

TRANCE X ADVANCED 1



產品規格

車架	
尺寸	S, M, L, XL
顏色	Arctic Light/Chrome
車架	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
前叉	Fox 36 Performance Elite, 150mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
避震器	Fox Float X Performance Elite, two-position LSC adjust, 185/52.5, custom tuned for Giant
COMPONENTS	
車把手	Giant Contact SL TR35, alloy, 780x35mm, 20mm rise
把手帶/套	Giant Tactal Pro Single Lock-On, 132x35mm
豎桿	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
座桿	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
坐墊	Giant Romero SL
踏板	N/A
DRIVETRAIN	
變速把手	SRAM AXS Pod, 1x12
前變速器	N/A
後變速器	SRAM GX Eagle AXS, T-Type
煞車系統	Shimano Deore XT BR-M8120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
煞車把手	Shimano Deore XT BL-M8100
飛輪	SRAM GX, T-Type, 10x52
鍊條	SRAM GX, T-Type
大齒盤	SRAM GX, T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET (B B)	SRAM DUB, Press Fit

輪組	
輪圈	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
花鼓	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
輻條	Sapim, 28, straight pull, DBL Technology
外胎	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
其他	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Price: NT\$188,000

車架幾何

車架	S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
座(立)管長 (mm)	400			425			450		
Seat Post Insertion Depth (mm)	280			305			330		
座(立)管角度	76.8° 77.2° 77.5°			76.8° 77.2° 77.5°			76.8° 77.2° 77.5°		
上管長度 (mm)	571 570 569			602 601 600			624 623 622		
頭管長度 (mm)	100			105			115		
頭管角度	64.4° 64.8° 65.1°			64.4° 64.8° 65.1°			64.4° 64.8° 65.1°		
前叉 (mm)	44			44			44		
Trail (mm)	134.1 131.3 128.4			134 131.3 128.5			133.9 131.3 128.5		
前後輪距 (mm)	1190 1190 1189			1222 1222 1221			1246 1246 1245		
後下叉長度 (mm)	440 439 438			440 439 438			440 439 438		
五通下降高度 (mm)	40 35 30			40 35 30			40 35 30		
頭碗至五通高度 (mm)	617 614 611			621 619 616			631 628 625		
頭碗至五通長度 (mm)	426 430 434			456 460 464			476 480 484		
上管至地面高度 (mm)	733 737 742			737 741 746			754 759 763		
把手寬 (mm)	800			800			800		
龍頭長度 (mm)	40			40			50		
曲柄長度 (mm)	165			170			170		
輪組尺寸	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。