

TRANCE X ADVANCED 2



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	S, M, L, XL
ЦВЯТ	Sangria/Chrome
РАМКА	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
ВИЛКА	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
ЗАДЕН АМОРТИСЬОР	Fox Float Performance, 185/52.5, custom tuned for Giant
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact TR35, alloy, 780x35mm, 20mm rise
ГРИПОВЕ	Giant Tactal Pro Single Lock-On, 132x35mm
ЛАПА	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
КОЛЧЕ ЗА СЕДАЛКА	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
СЕДАЛКА	Giant Romero SL
ПЕДАЛИ	N/A
DRIVETRAIN	
КОМАНДИ	Shimano SLX M-7100, I-Spec EV, 1x12
ПРЕДЕН ДЕРАЙЛЪОР	N/A
ЗАДЕН ДЕРАЙЛЪОР	Shimano SLX M-7100
СПИРАЧКИ	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
РЪКХОВАТКИ ЗА СПИРАЧКИ	Shimano Deore BL-M6100
КАСЕТА	Shimano SLX M7100, 10x51
ВЕРИГА	KMC X-12
КУРБЕЛ	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
СРЕДНА КАСЕТА	Shimano Press Fit

КАПЛИ	
ШИНИ	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
ГЛАВИНИ	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
СПИЦИ	Sapim, 28, straight pull, DBL Technology
ГУМИ	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
ЕКСТРИ	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

ГЕОМЕТРИЯ

РАМКА	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	76,8° 77,2° 77,5°			76,8° 77,2° 77,5°			76,8° 77,2° 77,5°			76,8° 77,2° 77,5°		
Top Tube Length (mm)	571 570 569			602 601 600			624 623 622			657 656 655		
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4° 64,8° 65,1°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134,1 131,3 128,4			134 131,3 128,5			133,9 131,3 128,5			133,9 131,3 128,5		
Wheelbase (mm)	1190 1190 1189			1222 1222 1221			1246 1246 1245			1281 1280 1280		
Chain Stay Length (mm)	440 439 438			440 439 438			440 439 438			440 439 438		
Bottom Bracket Drop (mm)	40 35 30			40 35 30			40 35 30			40 35 30		
Stack (mm)	617 614 611			621 619 616			631 628 625			640 637 634		
Обсер (mm)	426 430 434			456 460 464			476 480 484			507 510 514		
Stand Over Height (mm)	733 737 742			737 741 746			754 759 763			752 757 762		
Ширина на Кормило (mm)	800			800			800			800		
Дължина на Лапа (mm)	40			40			50			50		
Дължина на Курбел (mm)	165			170			170			170		
Размер на Каплите	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

All specifications listed are subject to change without notice.