# TRANCE X ADVANCED 2

## SPECS

| FRAME | |
|---|---|
| **SIZES** | S, M, L, XL |
| **COLORS** | Sangria/Chrome |
| **FRAME** | Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts |
| **FORK** | Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset |
| **SHOCK** | Fox Float Performance, 185/52.5, custom tuned for Giant |
| **COMPONENTS** | |
| **HANDLEBAR** | Giant Contact TR35, alloy, 780x35mm, 20mm rise |
| **GRIPS** | Giant Tactal Pro Single Lock-On, 132x35mm |
| **STEM** | Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm |
| **SEATPOST** | Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm |
| **SADDLE** | Giant Romero SL |
| **PEDALS** | N/A |
| **DRIVETRAIN** | |
| **SHIFTERS** | Shimano SLX M-7100, I-Spec EV, 1x12 |
| **FRONT DERAILLEUR** | N/A |
| **REAR DERAILLEUR** | Shimano SLX M-7100 |
| **BRAKES** | Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm |
| **BRAKE LEVERS** | Shimano Deore BL-M6100 |
| **CASSETTE** | Shimano SLX M7100, 10x51 |
| **CHAIN** | KMC X-12 |
| **CRANKSET** | Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm |
| **BOTTOM BRACKET** | Shimano Press Fit |

| WHEELS | |
|---|---|
| **RIMS** | Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology |
| **HUBS** | [F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt |
| **SPOKES** | Sapim, 28, straight pull, DBL Technology |
| **TIRES** | [F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless |
| **EXTRAS** | tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection |

## GEOMETRY

| FRAME | S | M | L | XL |
|---|---|---|---|---|
| | LOW \| MID \| HIGH | LOW \| MID \| HIGH | LOW \| MID \| HIGH | LOW \| MID \| H |
| Seat Tube Length (mm) | 400 | 425 | 450 | 475 |
| Seat Post Insertion Depth (mm) | 280 | 305 | 330 | 355 |
| Seat Tube Angle | 76,8° \| 77,2° \| 77,5° | 76,8° \| 77,2° \| 77,5° | 76,8° \| 77,2° \| 77,5° | 76,8° \| 77,2° \| |
| Top Tube Length (mm) | 571 \| 570 \| 569 | 602 \| 601 \| 600 | 624 \| 623 \| 622 | 657 \| 656 \| 65 |
| Head Tube Length (mm) | 100 | 105 | 115 | 125 |
| Head Tube Angle | 64,4° \| 64,8° \| 65,1° | 64,4° \| 64,8° \| 65,1° | 64,4° \| 64,8° \| 65,1° | 64,4° \| 64,8° \| |
| Fork Rake (mm) | 44 | 44 | 44 | 44 |
| Trail (mm) | 134,1 \| 131,3 \| 128,4 | 134 \| 131,3 \| 128,5 | 133,9 \| 131,3 \| 128,5 | 133,9 \| 131,3 \| |
| Wheelbase (mm) | 1190 \| 1190 \| 1189 | 1222 \| 1222 \| 1221 | 1246 \| 1246 \| 1245 | 1281 \| 1280 \| |
| Chain Stay Length (mm) | 440 \| 439 \| 438 | 440 \| 439 \| 438 | 440 \| 439 \| 438 | 440 \| 439 \| 43 |
| Bottom Bracket Drop (mm) | 40 \| 35 \| 30 | 40 \| 35 \| 30 | 40 \| 35 \| 30 | 40 \| 35 \| 30 |
| Stack (mm) | 617 \| 614 \| 611 | 621 \| 619 \| 616 | 631 \| 628 \| 625 | 640 \| 637 \| 63 |
| Reach (mm) | 426 \| 430 \| 434 | 456 \| 460 \| 464 | 476 \| 480 \| 484 | 507 \| 510 \| 51 |
| Stand Over Height (mm) | 733 \| 737 \| 742 | 737 \| 741 \| 746 | 754 \| 759 \| 763 | 752 \| 757 \| 76 |
| Handlebar Width (mm) | 800 | 800 | 800 | 800 |
| Stem Length (mm) | 40 | 40 | 50 | 50 |
| Crank Length (mm) | 165 | 170 | 170 | 170 |
| Wheel Size | [F] 29" [R | [F] 29" [R | [F] 29" [R | [F] 29" [R |

*All specifications listed are subject to change without notice.*