

TRANCE X ADVANCED 2



SPECIFIKACE

RÁM	
VELIKOSTI	S, M, L, XL
BARVA	Cryo Silver/Chrome
RÁM	Advanced Composite front and rear triangles, 140mm Maestro Suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
VIDLICE	Fox 36 Float Performance, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
TLUMIČ	Fox Float Performance, 185/52.5
KOMPONENTY	
ŘÍDÍTKA	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GRIPY	Giant Tactal Pro Single Lock-On, 132x35mm
PŘEDSTAVEC	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEDOVKA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SEDLO	Giant Romero SL
PEDÁLY	-
OSAZENÍ	
ŘAZENÍ	SRAM Eagle 90, 1x12
PŘESMYKAČ	-
PŘEHAZOVAČKA	SRAM Eagle 90 Transmission
BRZDY	TRP EVO Expert HD-M8040, hydraulic, TRP-SO6E, 6-bolt rotors [F]180mm, [R]180mm
BRZDOVÉ PÁKY	TRP EVO Expert
KAZETA	SRAM XS 1270, 10x52
ŘETĚZ	SRAM 70 Transmission
KLIKY	SRAM Eagle 90 T-Type, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm
STŘED	SRAM DUB, Press Fit

KOLA	
RÁFKY	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NÁBOJE	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, MicroSpline driver body
DRÁTY	Sapim, 28, straight pull, DBL Technology
PLÁŠTĚ	[F] Maxxis Assegai, 29x2.5 WT, 60 tpi, MaxxTerra, EXO, TR [R] Maxxis DHR II 29x2.4 WT, 60 tpi, MaxxTerra, TR, tubeless
DOPLŇKY	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Cena: 149 999 Kč

GEOMETRIE

RÁM	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Délka sedlové trubky (mm)	400			425			450			475		
Max. zasunutí sedlovky (mm)	280			305			330			355		
Úhel sedlové trubky	76,8° 77,2° 77,5°			76,8° 77,2° 77,5°			76,8° 77,2° 77,5°			76,8° 77,2° 77,5°		
Délka horní trubky (mm)	571 570 569			602 601 600			624 623 622			657 656 655		
Délka hlavové trubky (mm)	100			105			115			125		
Úhel hlavové trubky	64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4° 64,8° 65,1°		
Offset vidlice (mm)	44			44			44			44		
Trail (mm)	134,1 131,3 128,4			134 131,3 128,5			133,9 131,3 128,5			133,9 131,3 128,5		
Rozvor (mm)	1190 1190 1189			1222 1222 1221			1246 1246 1245			1281 1280 1279		
Délka řetězové vzpěry (mm)	440 439 438			440 439 438			440 439 438			440 439 438		
Bottom Bracket Drop (mm)	40 35 30			40 35 30			40 35 30			40 35 30		
Stack (mm)	617 614 611			621 619 616			631 628 625			640 637 634		
Reach (mm)	426 430 434			456 460 464			476 480 484			507 510 514		
Výška rámu od země (mm)	733 737 742			737 741 746			754 759 763			752 757 762		
Šířka řídítek (mm)	800			800			800			800		
Délka představce (mm)	40			40			50			50		
Délka klik (mm)	165			170			170			170		

Děláme vše pro to, aby veškeré údaje na tomto webu byly správné a aktuální. Přesto si ale musíme vyhradit právo na případné změny specifikací, barevného provedení a cen, a to bez předchozího upozornění. Děkujeme za pochopení.