

TRANCE X ADVANCED 2



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, L, XL
FARVER	Sangria/Chrome
RAMME	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FORGAFFEL	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
BAGDÆMPER	Fox Float Performance, 185/52.5, custom tuned for Giant
KOMPONENTER	
STYR	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GREB / STYRBÅND	Giant Tactal Pro Single Lock-On, 132x35mm
FREMPIND	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SADELPIND	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADEL	Giant Romero SL
PEDALER	N/A
GEARGRUPPE	
SKIFTEGREB	Shimano SLX M-7100, I-Spec EV, 1x12
FORSKIFTER	N/A
BAGSKIFTER	Shimano SLX M-7100
BREMSE	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BREMSEGREB	Shimano Deore BL-M6100
KASSETTE	Shimano SLX M7100, 10x51
KÆDE	KMC X-12
KRANKSÆT	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
KRANKBOKS	Shimano Press Fit

HJUL	
FÆLGE	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NAV	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
EGER	Sapim, 28, straight pull, DBL Technology
D/ÆK	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EKSTRA	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Pris: 46.499,00 kr.

GEOMETRI

RAMME	S	M	L	XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH	LOW MID
Sadelrørslængde (mm)	400	425	450	475
Sadelpindindsætningsdybde (mm)	280	305	330	355
Sadelrøsvinkel	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2°
Overrørslængde (mm)	571 570 569	602 601 600	624 623 622	657 656
Kronrørslængde (mm)	100	105	115	125
Kronrøsvinkel	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8
Forgaffel fremspring (rake) (mm)	44	44	44	44
Sti (mm)	134,1 131,3 128,4	134 131,3 128,5	133,9 131,3 128,5	133,9 131,
Akselafstand (mm)	1190 1190 1189	1222 1222 1221	1246 1246 1245	1281 1280
Kædestagslængde (mm)	440 439 438	440 439 438	440 439 438	440 439
Krankboks drop (mm)	40 35 30	40 35 30	40 35 30	40 35 30
Stack (mm)	617 614 611	621 619 616	631 628 625	640 637
Reach (mm)	426 430 434	456 460 464	476 480 484	507 510
Skridthøjde (mm)	733 737 742	737 741 746	754 759 763	752 757
Styrbredde (mm)	800	800	800	800
Frempindslængde (mm)	40	40	50	50
Pedalarmslængde (mm)	165	170	170	170
Hjulstørrelse	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Alle de anførte specifikationer kan ændres uden varsel.