

TRANCE X ADVANCED 2



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Cryo Silver
FRAME	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, flip chip 3 position, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, integrated downtube storage, 55mm Chainline
FORK	Fox 36 Float Performance, 150mm, GRIP damper, 3 position, 15x110mm Kabolt X thru-axle, 44mm offset
SHOCK	Fox Float Performance, 2 position, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 20mm rise
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Eagle 90, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Eagle 90 Transmission
BRAKES	TRP EVO Expert, hydraulic, TRP 2.3mm rotors [F]203mm, [R]180mm
BRAKE LEVERS	TRP EVO Expert
CASSETTE	SRAM XS 1270, 10x52
CHAIN	SRAM 70 Transmission
CRANKSET	SRAM Eagle 90 Transmission, 30t, 55mm chainline S:165mm, M:165mm, L:165mm, XL:165mm
BOTTOM BRACKET	SRAM DUB, Press Fit

WHEELS	
RIMS	Giant TRX Hookless Tubeless ready Carbon, 29", 30mm inner width
HUBS	[F] Giant TRX MTB Alloy Hub, 6 Bolt, 28H [R] Giant TRX MTB Alloy Hub, SRAM XD Drive Body Pawl Driver (Pawl 36x2 T), 28H
SPOKES	Sapim Laser
TYRES	[F] Maxxis Assegai 29x2.5 WT, MaxxTerra, EXO, TR [R] Maxxis Minion DHR II 29x2.4 WT, MaxxTerra, EXO, TR tubeless
EXTRAS	Tubeless prepared, 3M tailgate protector, down tube and chainstay protection
LIMITS	
MAX TYRE CLEARANCE	2.5"
MAX CHAINRING SIZE	34t

Price: \$7,499.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	76.8° 77.2° 77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°
Top Tube Length (mm)	571 570 569	602	601	600	624	623	622	657	656	65		
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	64.4° 64.8° 65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.1 131.3 128.4	134	131.3	128.5	133.9	131.3	128.5	133.9	131.3			
Wheelbase (mm)	1190 1190 1189	1222	1222	1221	1246	1246	1245	1281	1280			
Chain Stay Length (mm)	440 439 438	440	439	438	440	439	438	440	439	43		
Bottom Bracket Drop (mm)	40 35 30	40	35	30	40	35	30	40	35	30		
Stack (mm)	617 614 611	621	619	616	631	628	625	640	637	63		
Reach (mm)	426 430 434	456	460	464	476	480	484	507	510	51		
Stand Over Height (mm)	733 737 742	737	741	746	754	759	763	752	757	76		
Stem Length (mm)	40			40			50			50		
Crank Length (mm)	165			170			170			170		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.