

TRANCE X ADVANCED 2



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Sangria/Chrome
FRAME	Advanced-grade composite front and rear triangles, 140mm Maestro suspension, flip chip - Maestro 3, flip chip - headset, 12x148mm thru-axle, integrated downtube storage
FORK	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
SHOCK	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 20mm rise, alloy, 780x35mm
GRIPS	Giant Tactal Pro single lock-on
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch Adjustable, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L/XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano SLX M-7100, I-Spec EV, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX M-7100
BRAKES	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano Deore BL-M6100
CASSETTE	Shimano SLX M7100, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano Press Fit

WHEELS	
RIMS	Giant TRX WheelSystem, carbon rim, 30mm IW, 40mm OW, 21mm H, Wide Guard technology, [F] 29, [R] 29
HUBS	[F] Giant MTB alloy, 6-bolt, sealed [R] Giant MTB alloy, 6 bolt, 72t POE, 6-pawl, sealed
SPOKES	Sapim Laser straight pull, DBL technology
TIRES	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, integrated down tube storage bag

Suggested Retail Price (CDN): \$5,899.00

FRAME GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°
Top Tube Length (mm)	571	570	569	602	601	600	624	623	622	657	656	655
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.1	131.3	128.4	134	131.3	128.5	133.9	131.3	128.5	133.9	131.3	128.5
Wheelbase (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1280	1279
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Bottom Bracket Drop (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	634
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	514
Stand Over Height (mm)	733	737	742	737	741	746	754	759	763	752	757	761
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

All prices and specifications are subject to change without notice.