

TRANCE X ADVANCED 2



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Gloss Cryo Silver/Chrome
FRAME	Advanced-grade composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FORK	Fox 36 Float Performance, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
SHOCK	Fox Float Performance, 185/52.5
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single Lock-On, 132x35mm
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero SL
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	SRAM Eagle 90, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Eagle 90 Transmission
BRAKES	TRP EVO Expert HD-M8040, hydraulic, TRP-SO6E, 6-bolt rotors [F]180mm, [R]180mm
BRAKE LEVERS	TRP EVO Expert
CASSETTE	SRAM XS 1270, 10x52
CHAIN	SRAM 70 Transmission
CRANKSET	SRAM Eagle 90 T-Type, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm
BOTTOM BRACKET	SRAM DUB, Press Fit

WHEELS	
RIMS	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
HUBS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, MicroSpline driver body
SPOKES	Sapim, 28, straight pull, DBL Technology
TYRES	[F] Maxxis Assegai, 29x2.5 WT, 60 tpi, MaxxTerra, EXO, TR [R] Maxxis DHR II 29x2.4 WT, 60 tpi, MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tyre size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Price: £4,799.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	
Top Tube Length (mm)	571	570	569	602	601	600	624	623	622	657	656	65
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.1	131.3	128.4	134	131.3	128.5	133.9	131.3	128.5	133.9	131.3	
Wheelbase (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1280	
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	43
Bottom Bracket Drop (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	63
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	51
Stand Over Height (mm)	733	737	742	737	741	746	754	759	763	752	757	76
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			50			50		
Crank Length (mm)	165			170			170			170		

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.