

TRANCE X ADVANCED 2



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Sangria
CUADRO	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
HORQUILLA	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
AMORTIGUADOR	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPONENTES	
MANILLAR	Giant Contact TR35, alloy, 780x35mm, 20mm rise
PUÑOS	Giant Tactal Pro Single Lock-On, 132x35mm
POTENCIA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
TIJA DE SILLÍN	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SILLÍN	Giant Romero SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano SLX M-7100, I-Spec EV, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	Shimano SLX M-7100
FRENOS	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
PALANCAS DE FRENOS	Shimano Deore BL-M6100
CASETTE	Shimano SLX M7100, 10x51
CADENA	KMC X-12
JGO. PLATOS Y BIELAS	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
CAJA DE PEDALIER	Shimano Press Fit

RUEDAS	
LLANTAS	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
BUJES	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
RADIOS	Sapim, 28, straight pull, DBL Technology
CUBIERTAS	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Precio: 5.499,00 €

GEOMETRÍA

CUADRO	S	M	L	XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Longitud del tubo del sillín (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	280	305	330	355
Ángulo del tubo del sillín	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°
Longitud del tubo superior (mm) (mm)	571 570 569	602 601 600	624 623 622	657
Longitud del tubo de dirección (mm) (mm)	100	105	115	125
Ángulo del tubo de dirección	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°
Inclinación de la horquilla (mm)	44	44	44	44
Trail (mm) (mm)	134,1 131,3 128,4	134 131,3 128,5	133,9 131,3 128,5	133
Distancia entre ejes (mm) (mm)	1190 1190 1189	1222 1222 1221	1246 1246 1245	128
Longitud de la vaina (mm) (mm)	440 439 438	440 439 438	440 439 438	440
Caída del eje de pedalier (mm) (mm)	40 35 30	40 35 30	40 35 30	40 35 30
Stack (mm) (mm)	617 614 611	621 619 616	631 628 625	640
Reach (mm) (mm)	426 430 434	456 460 464	476 480 484	507
Altura del suelo al tubo (mm) (mm)	733 737 742	737 741 746	754 759 763	752
Ancho del manillar (mm) (mm)	800	800	800	800
Longitud de la potencia (mm) (mm)	40	40	50	50
Longitud de las bielas (mm) (mm)	165	170	170	170
Tamaño de ruedas	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.