

TRANCE X ADVANCED 2

GIANT



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, L, XL
VÄRIT	Sangria/Chrome
RUNKO	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
HAARUKKA	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
ISKUNVAIMENNIN	Fox Float Performance, 185/52.5, custom tuned for Giant
KOMONENTIT	
OHJAUSTANKO	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GRIPIT	Giant Tactal Pro Single Lock-On, 132x35mm
OHJAINKANNATIN	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SATULATOLPPA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SATULA	Giant Romero SL
POLKIMET	N/A
VOIMANSIIRTO	
VAIHDEVIPU	Shimano SLX M-7100, I-Spec EV, 1x12
ETUVAIHTAJA	N/A
TAKAVAIHTAJA	Shimano SLX M-7100
JARRUT	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
JARRUKAHVAT	Shimano Deore BL-M6100
RATASPAKKA	Shimano SLX M7100, 10x51
KETJUT	KMC X-12
KAMPISARJA	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
KESKIÖ	Shimano Press Fit

RENKAAT	
VANTEET	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NAVAT	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
PINNAT	Sapim, 28, straight pull, DBL Technology
RENKAAT	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
LISÄTIEDOT	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Suositusuhinta: 6 219,00 €

GEOMETRIA

RUNKO	S
	LOW MID HIGH
Satulaputken pituus (mm)	400
Satulatolpan asennussyvyys (mm)	280
Satulaputken kulma	76,8° 77,2° 77,5°
Vaakaputken pituus (mm)	571 570 569
Emäputken pituus (mm)	100
Emäputken kulma	64,4° 64,8° 65,1°
Haarukan offset (mm)	44
Trail-mitta (mm)	134,1 131,3 128,4
Akseliväli (mm)	1190 1190 1189
Takahaarukan alaputken pituus (mm)	440 439 438
Keskiön pudotus (mm)	40 35 30
Stack-mitta (mm)	617 614 611
Reach-mitta (mm)	426 430 434
Standover-mitta (mm)	733 737 742
Ohjaustangon leveys (mm)	800
Ohjainkannattimen pituus (mm)	40
Kammen pituus (mm)	165
Rengaskoko	[F] 29" [R]

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.