

TRANCE X ADVANCED 2



SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Sangria/Chrome
FRAME	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
VOORVORK	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
DEMPER	Fox Float Performance, 185/52.5, custom tuned for Giant
ONDERDELEN	
STUUR	Giant Contact TR35, alloy, 780x35mm, 20mm rise
HANDVATTEN	Giant Tactal Pro Single Lock-On, 132x35mm
STUURPEN	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
ZADELPEN	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
ZADEL	Giant Romero SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	Shimano SLX M-7100, I-Spec EV, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	Shimano SLX M-7100
REMMEN	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
REMHENDELS	Shimano Deore BL-M6100
CASSETTE	Shimano SLX M7100, 10x51
AANDRIJVING	KMC X-12
CRANKSET	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano Press Fit

WIELSET	
VELGEN	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NAVEN	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
SPAKEN	Sapim, 28, straight pull, DBL Technology
BANDEN	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRA'S	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Adviesprijs: € 5.999,00

GEOMETRIE

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Zitbuis Lengte (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Zitbuis Hoek	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°
Frame Lengte (horizontaal) (mm)	571	570	569	602	601	600	624	623	622	657	656	655
Balhoofdbuis Lengte (mm)	100			105			115			125		
Balhoofdbuis Hoek	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°
Vork Sprong (mm)	44			44			44			44		
Naloop (mm)	134,1	131,3	128,4	134	131,3	128,5	133,9	131,3	128,5	133,9	131,3	128,5
Wielbasis (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1280	1279
Liggende achtervork lengte (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Bottom Bracket Drop (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	634
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	514
Stand Over Height (mm)	733	737	742	737	741	746	754	759	763	752	757	761
Stuur breedte (mm)	800			800			800			800		
Stuurpen Lengte (mm)	40			40			50			50		
Cranklengte (mm)	165			170			170			170		
Wielmaat	[F] 29" [R] 27.5"			[F] 29" [R] 27.5"			[F] 29" [R] 27.5"			[F] 29" [R] 27.5"		

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.