

TRANCE X ADVANCED 2



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Sangria/Chrome
CADRE	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FOURCHE	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
AMORTISSEUR	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPOSANTS	
CINTRE	Giant Contact TR35, alloy, 780x35mm, 20mm rise
POIGNÉES	Giant Tactal Pro Single Lock-On, 132x35mm
POTENCE	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
TIGE DE SELLE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLE	Giant Romero SL
PÉDALES	N/A
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano SLX M-7100, I-Spec EV, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano SLX M-7100
FREINS	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
LEVIER DE FREIN	Shimano Deore BL-M6100
CASSETTE	Shimano SLX M7100, 10x51
CHAÎNE	KMC X-12
PÉDALIER	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
PÉDALIER	Shimano Press Fit

ROUES	
JANTES	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
MOYEUX	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
RAYONS	Sapim, 28, straight pull, DBL Technology
PNEUS	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

GÉOMÉTRIE

CADRE	S			M			L			XL		
	LOW MID HIGH			LOW MID HIGH			LOW MID HIGH			LOW MID HIGH		
Longueur de tube de selle (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Angle de tube de selle	76,8° 77,2° 77,5°			76,8° 77,2° 77,5°			76,8° 77,2° 77,5°			76,8° 77,2° 77,5°		
Longueur du tube supérieur (mm)	571 570 569			602 601 600			624 623 622			657 656 655		
Longueur du tube de direction (mm)	100			105			115			125		
Angle du tube de direction	64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4° 64,8° 65,1°		
Déport de fourche (mm)	44			44			44			44		
Chasse (mm)	134,1 131,3 128,4			134 131,3 128,5			133,9 131,3 128,5			133,9 131,3 128,5		
Empattement (mm)	1190 1190 1189			1222 1222 1221			1246 1246 1245			1281 1281 1280		
Longueur des bases (mm)	440 439 438			440 439 438			440 439 438			440 439 438		
Hauteur du boîtier de pédalier (mm)	40 35 30			40 35 30			40 35 30			40 35 30		
Stack (mm)	617 614 611			621 619 616			631 628 625			640 637 634		
Reach (mm)	426 430 434			456 460 464			476 480 484			507 510 513		
Hauteur d'enjambement (mm)	733 737 742			737 741 746			754 759 763			752 757 761		
Largeur de cintre (mm)	800			800			800			800		
Longueur de potence (mm)	40			40			50			50		
Longueur des manivelles (mm)	165			170			170			170		
Diamètre des roues	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.