

TRANCE X ADVANCED 2



TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Sangria/Chrome
CADRE	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FOURCHE	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
AMORTISSEUR	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPOSANTS	
CINTRE	Giant Contact TR35, alloy, 780x35mm, 20mm rise
POIGNÉES	Giant Tactal Pro Single Lock-On, 132x35mm
POTENCE	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
TIGE DE SELLE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLE	Giant Romero SL
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	Shimano SLX M-7100, I-Spec EV, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano SLX M-7100
FREINS	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
LEVIER DE FREIN	Shimano Deore BL-M6100
CASSETTE	Shimano SLX M7100, 10x51
CHAÎNE	KMC X-12
PÉDALIER	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOITIER DE PÉDALIER	Shimano Press Fit

ROUES	
JANTES	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
MOYEURS	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
RAYONS	Sapim, 28, straight pull, DBL Technology
PNEUS	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 5 500,00 €

GÉOMÉTRIE

CADRE	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longueur de tube de selle (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Angle de tube de selle	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°
Longueur du tube supérieur (mm)	571	570	569	602	601	600	624	623	622	657	656	655
Longueur du tube de direction (mm)	100			105			115			125		
Angle du tube de direction	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°
Déport de fourche (mm)	44			44			44			44		
Trail (mm)	134,1	131,3	128,4	134	131,3	128,5	133,9	131,3	128,5	133,9	131,3	128,4
Empattement (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1281	1280
Longueur des bases (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Drop du boîtier de pédalier (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	634
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	514
Hauteur en statique (mm)	733	737	742	737	741	746	754	759	763	752	757	761
Largeur de cintre (mm)	800			800			800			800		
Longueur de potence (mm)	40			40			50			50		
Longueur des manivelles (mm)	165			170			170			170		
Diamètre des roues	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.