

TRANCE X ADVANCED 2



SPECIFIKACIJE

OKVIR	
VELIČINE	S, M, L, XL
BOJE	Sangria/Chrome
OKVIR	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
VILICA	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
AMORTIZER	Fox Float Performance, 185/52.5, custom tuned for Giant
KOMPONENTE	
VOLAN	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single Lock-On, 132x35mm
LULA VOLANA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
CIJEV SJEDALA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SJEDALO	Giant Romero SL
PEDALE	N/A
POGON	
RUČICE MJENJAČA	Shimano SLX M-7100, I-Spec EV, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	Shimano SLX M-7100
KOČNICE	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
RUČICE KOČNICA	Shimano Deore BL-M6100
KAZETA	Shimano SLX M7100, 10x51
LANAC	KMC X-12
POGON	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
OSOVINA POGONA (BB)	Shimano Press Fit

KOTAČI	
OBRUČI	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NABE	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
ŽBICE	Sapim, 28, straight pull, DBL Technology
GUME	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
DODACI	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

GEOMETRIJA

OKVIR	S	M
	LOW MID HIGH	LOW MID HIGH
Dužina cijevi sjedala (mm)	400	425
Seat Post Insertion Depth (mm)	280	305
Kut cijevi sjedala	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°
Dužina gornje cijevi (mm)	571 570 569	602 601 600
Dužina prednje cijevi (mm)	100	105
Kut vilice	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°
Zakrivljenost vilice (offset) (mm)	44	44
Staza (mm)	134,1 131,3 128,4	134 131,3 128,5
Međuosovinski razmak kotača (mm)	1190 1190 1189	1222 1222 1221
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	440 439 438	440 439 438
Položaj osovine pogona (mm)	40 35 30	40 35 30
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	617 614 611	621 619 616
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	426 430 434	456 460 464
Prekoračna visina (mm)	733 737 742	737 741 746
Širina volana (mm)	800	800
Dužina lule volana (mm)	40	40
Dužina poluge pedale (mm)	165	170
Veličina kotača	[F] 29" [R]	[F] 29" [R]

Sve navedene specifikacije podložne su promjeni bez prethodne najave.