

TRANCE X ADVANCED 2



FELSZERELTSÉG

VÁZ	
MÉRETEK	S, M, L, XL
SZÍN	Sangria/Chrome
VÁZ	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
VILLA	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
RUGÓSTAG	Fox Float Performance, 185/52.5, custom tuned for Giant
ALKATRÉSZEK	
KORMÁNY	Giant Contact TR35, alloy, 780x35mm, 20mm rise
MARKOLAT	Giant Tactal Pro Single Lock-On, 132x35mm
KORMÁNYSZÁR	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
NYEREGCSŐ	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
NYEREG	Giant Romero SL
PEDÁLOK	N/A
HAJTÁS	
VÁLTÓKAROK	Shimano SLX M-7100, I-Spec EV, 1x12
ELSŐ VÁLTÓ	N/A
HÁTSÓ VÁLTÓ	Shimano SLX M-7100
FÉKEK	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
FÉKKAROK	Shimano Deore BL-M6100
FOGASKOSZORÚ	Shimano SLX M7100, 10x51
LÁNC	KMC X-12
HAJTÓMŰ	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
KÖZÉPCSAPÁGY	Shimano Press Fit

KEREKEK	
FELNIK	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
AGYAK	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
KÜLLŐK	Sapim, 28, straight pull, DBL Technology
KÜLSŐK	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
KIEGÉSZÍTŐK	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Ár: 2 569 900,00 Ft

GEOMETRIA

VÁZ	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Nyeregcső hossz (mm)	400			425			450			475
Ülésoszlop behelyezési mélysége (mm)	280			305			330			355
Nyeregcső szög	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°
Felsőcső hossz (mm)	571	570	569	602	601	600	624	623	622	657
Fejcső hossz (mm)	100			105			115			125
Fejcsőszög	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°
Fork Rake (mm)	44			44			44			44
Trail (mm)	134,1	131,3	128,4	134	131,3	128,5	133,9	131,3	128,5	133,9
Keréktávolság (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281
Láncvilla hossz (mm)	440	439	438	440	439	438	440	439	438	440
Középcsapágy esés (mm)	40	35	30	40	35	30	40	35	30	40
Stack (mm)	617	614	611	621	619	616	631	628	625	640
Reach (mm)	426	430	434	456	460	464	476	480	484	507
Átlépési magasság (mm)	733	737	742	737	741	746	754	759	763	752
Kormányzélesség (mm)	800			800			800			800
Kormányzár hossz (mm)	40			40			50			50
Hajtókar hossz (mm)	165			170			170			170
Kerékméret	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29"

A felsorolt leírások előzetes értesítés nélkül is változhatnak.