

TRANCE X ADVANCED 2

GIANT



SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Sangria/Chrome
TELAIO	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FORCELLA	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
AMMORTIZZATORE	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPONENTISTICA	
MANUBRIO	Giant Contact TR35, alloy, 780x35mm, 20mm rise
MANOPOLE	Giant Tactal Pro Single Lock-On, 132x35mm
ATTACCO MANUBRIO	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
REGGISELLA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLA	Giant Romero SL
PEDALI	N/A
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano SLX M-7100, I-Spec EV, 1x12
DERAGLIATORE ANTERIORE	N/A
DERAGLIATORE POSTERIORE	Shimano SLX M-7100
FRENI	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
COMANDI FRENO	Shimano Deore BL-M6100
PACCO PIGNONI	Shimano SLX M7100, 10x51
CATENA	KMC X-12
GUARNITURA	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
MOVIMENTO CENTRALE	Shimano Press Fit

RUOTE	
CERCHI	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
MOZZI	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
RAGGI	Sapim, 28, straight pull, DBL Technology
COPERTONI	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRA	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Prezzo: 5.899,00 €

GEOMETRIA

TELAIO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Lunghezza Tubo Sella (mm)	400			425			450			475
Profondità inserimento reggisella (mm)	280			305			330			355
Angolo Tubo Sella	76,8° 77,2° 77,5°			76,8° 77,2° 77,5°			76,8° 77,2° 77,5°			76,8°
Lunghezza Tubo Orizzontale (mm)	571 570 569			602 601 600			624 623 622			657 656 655
Lunghezza Tubo Sterzo (mm)	100			105			115			125
Angolo Sterzo	64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4°
Rake Forcella (mm)	44			44			44			44
Avancorsa (mm)	134,1 131,3 128,4			134 131,3 128,5			133,9 131,3 128,5			133,9
Interasse (mm)	1190 1190 1189			1222 1222 1221			1246 1246 1245			1281
Lunghezza Carro Posteriore (mm)	440 439 438			440 439 438			440 439 438			440 439 438
Drop Movimento Centrale (mm)	40 35 30			40 35 30			40 35 30			40 35 30
Stack (mm)	617 614 611			621 619 616			631 628 625			640 637 634
Reach (mm)	426 430 434			456 460 464			476 480 484			507 511 515
Altezza stand over (mm)	733 737 742			737 741 746			754 759 763			752 756 760
Larghezza Manubrio c/c (mm)	800			800			800			800
Lunghezza Attacco Manubrio (mm)	40			40			50			50
Lunghezza Pedivella (mm)	165			170			170			170
Dimensione Ruote	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.