

# TRANCE X ADVANCED 2

**GIANT**



## SPECIFICATIES

| FRAME            |  |
|------------------|--|
| MATEN            | S, M, L, XL  |
| KLEUREN          | Sangria/Chrome   |
| FRAME            | Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts |
| VOORVORK         | Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset  |
| DEMPER           | Fox Float Performance, 185/52.5, custom tuned for Giant  |
| ONDERDELEN       |  |
| STUUR            | Giant Contact TR35, alloy, 780x35mm, 20mm rise   |
| HANDVATTEN       | Giant Tactal Pro Single Lock-On, 132x35mm  |
| STUURPEN         | Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm  |
| ZADELPEN         | Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm   |
| ZADEL            | Giant Romero SL  |
| PEDALEN          | N/A  |
| AFMONTAGE        |  |
| SHIFTERS         | Shimano SLX M-7100, I-Spec EV, 1x12  |
| VOORDERAILLEUR   | N/A  |
| ACHTERDERAILLEUR | Shimano SLX M-7100   |
| REMMEN           | Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm  |
| REMHENDELS       | Shimano Deore BL-M6100   |
| CASSETTE         | Shimano SLX M7100, 10x51   |
| AANDRIJVING      | KMC X-12   |
| CRANKSET         | Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm   |
| BOTTOM BRACKET   | Shimano Press Fit  |

| WIELSET |  |
|---------|--|
| VELGEN  | Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology                    |
| NAVEN   | [F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt  |
| SPAKEN  | Sapim, 28, straight pull, DBL Technology   |
| BANDEN  | [F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless |
| EXTRA'S | tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection           |

Adviesprijs: € 5.999,00

## GEOMETRIE

| FRAME                           | S           |       |       | M           |       |       | L           |       |       | XL          |       |       |
|---------------------------------|-------------|-------|-------|-------------|-------|-------|-------------|-------|-------|-------------|-------|-------|
|                                 | LOW         | MID   | HIGH  | LOW         | MID   | HIGH  | LOW         | MID   | HIGH  | LOW         | MID   | HIGH  |
| Zitbuis lengte (mm)             | 400         |       |       | 425         |       |       | 450         |       |       | 475         |       |       |
| Seat Post Insertion Depth (mm)  | 280         |       |       | 305         |       |       | 330         |       |       | 355         |       |       |
| Zitbuis hoek                    | 76,8°       | 77,2° | 77,5° | 76,8°       | 77,2° | 77,5° | 76,8°       | 77,2° | 77,5° | 76,8°       | 77,2° | 77,5° |
| Frame Lengte (horizontaal) (mm) | 571         | 570   | 569   | 602         | 601   | 600   | 624         | 623   | 622   | 657         | 656   | 656   |
| Balhoofdbuis Lengte (mm)        | 100         |       |       | 105         |       |       | 115         |       |       | 125         |       |       |
| Balhoofdbuis Hoek               | 64,4°       | 64,8° | 65,1° | 64,4°       | 64,8° | 65,1° | 64,4°       | 64,8° | 65,1° | 64,4°       | 64,8° | 64,8° |
| Vork Sprong (mm)                | 44          |       |       | 44          |       |       | 44          |       |       | 44          |       |       |
| Naloop (mm)                     | 134,1       | 131,3 | 128,4 | 134         | 131,3 | 128,5 | 133,9       | 131,3 | 128,5 | 133,9       | 131,3 | 128,5 |
| Wielbasis (mm)                  | 1190        | 1190  | 1189  | 1222        | 1222  | 1221  | 1246        | 1246  | 1245  | 1281        | 1280  | 1280  |
| Liggende achtervork lengte (mm) | 440         | 439   | 438   | 440         | 439   | 438   | 440         | 439   | 438   | 440         | 439   | 438   |
| Bottom Bracket Drop (mm)        | 40          | 35    | 30    | 40          | 35    | 30    | 40          | 35    | 30    | 40          | 35    | 30    |
| Stack (mm)                      | 617         | 614   | 611   | 621         | 619   | 616   | 631         | 628   | 625   | 640         | 637   | 634   |
| Reach (mm)                      | 426         | 430   | 434   | 456         | 460   | 464   | 476         | 480   | 484   | 507         | 510   | 514   |
| Stand Over Height (mm)          | 733         | 737   | 742   | 737         | 741   | 746   | 754         | 759   | 763   | 752         | 757   | 761   |
| Stuur breedte (mm)              | 800         |       |       | 800         |       |       | 800         |       |       | 800         |       |       |
| Stuurpen Lengte (mm)            | 40          |       |       | 40          |       |       | 50          |       |       | 50          |       |       |
| Cranklengte (mm)                | 165         |       |       | 170         |       |       | 170         |       |       | 170         |       |       |
| Wielmaat                        | [F] 29" [R] |       |       | [F] 29" [R] |       |       | [F] 29" [R] |       |       | [F] 29" [R] |       |       |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.