

TRANCE X ADVANCED 2



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	S, M, L, XL
FARBY	Sangria/Chrome
RÁM	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
VIDLICA	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
TLMIČ	Fox Float Performance, 185/52.5, custom tuned for Giant
KOMPONENTY	
RIADIDLÁ	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GRIPY	Giant Tactal Pro Single Lock-On, 132x35mm
PREDSTAVEC	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEDOVKA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SEDADLO	Giant Romero SL
PEDÁLE	N/A
POHON	
RADENIE	Shimano SLX M-7100, I-Spec EV, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	Shimano SLX M-7100
BRZDY	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BRZDOVÉ PÁKY	Shimano Deore BL-M6100
KAZETA	Shimano SLX M7100, 10x51
REŤAZ	KMC X-12
KLUKY	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
STREDOVÉ ZLOŽENIE	Shimano Press Fit

KOLESÁ	
RÁFIKY	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NÁBOJE	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
ŠPICE	Sapim, 28, straight pull, DBL Technology
PNEUMATIKY	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
DOPLNKY	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Cena: nová cena 5 099 € / pôvodná cena 5 999 €

GEOMETRIA

RÁM	S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dĺžka sedlovej trubky (mm)	400			425			450		
Hĺbka vloženia sedlovky (mm)	280			305			330		
Uhol sedlovej trubky	76,8° 77,2° 77,5°			76,8° 77,2° 77,5°			76,8° 77,2° 77,5°		
Dĺžka hornej rámovej trubky (mm)	571 570 569			602 601 600			624 623 622		
Dĺžka hlavovej trubky (mm)	100			105			115		
Uhol hlavovej trubky	64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4° 64,8° 65,1°		
Offset vidlice (mm)	44			44			44		
Trail (mm)	134,1 131,3 128,4			134 131,3 128,5			133,9 131,3 128,5		
Rázvor (mm)	1190 1190 1189			1222 1222 1221			1246 1246 1245		
Dĺžka zadnej stavby (mm)	440 439 438			440 439 438			440 439 438		
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	40 35 30			40 35 30			40 35 30		
Stack - výška riadenia (mm)	617 614 611			621 619 616			631 628 625		
Reach (mm)	426 430 434			456 460 464			476 480 484		
Výška rámu od zeme (mm)	733 737 742			737 741 746			754 759 763		
Šírka riaditok (mm)	800			800			800		
Dĺžka predstavca (mm)	40			40			50		
Dĺžka klúku (mm)	165			170			170		
Rozmer kolies	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.