

TRANCE X ADVANCED 2



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Sangria/Chrome
OKVIR	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
VILICE	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
AMORTIZER	Fox Float Performance, 185/52.5, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single Lock-On, 132x35mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
OPORA SEDEŽA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SEDEŽ	Giant Romero SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	Shimano SLX M-7100, I-Spec EV, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano SLX M-7100
ZAVORE	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
ZAVORNE ROČICE	Shimano Deore BL-M6100
VERIŽNIK	Shimano SLX M7100, 10x51
VERIGA	KMC X-12
GONILKE Z VERIŽNIKI	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano Press Fit

OBROČNIKI	
OBROČI	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
PESTA	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
NAPERE	Sapim, 28, straight pull, DBL Technology
PLAŠČI	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
DODATKI	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

GEOMETRIJA

OKVIR	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	L
Dolžina sedežne cevi (mm)	400			425			450			4
Seat Post Insertion Depth (mm)	280			305			330			3
Kot sedežne cevi	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	7
Top Tube Length (mm)	571	570	569	602	601	600	624	623	622	6
Višina glave okvirja (mm)	100			105			115			1
Krmilni kot	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	6
Zamik vpetja osi (mm)	44			44			44			4
Trail (mm)	134,1	131,3	128,4	134	131,3	128,5	133,9	131,3	128,5	1
Medosna razdalja (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1
Dolžina cevi ob verigi (mm)	440	439	438	440	439	438	440	439	438	4
Bottom Bracket Drop (mm)	40	35	30	40	35	30	40	35	30	4
Oddaljenost zgornje cevi od gonilne osi (mm)	617	614	611	621	619	616	631	628	625	6
Doseg (mm)	426	430	434	456	460	464	476	480	484	5
Višina zgornje cevi (mm)	733	737	742	737	741	746	754	759	763	7
Širina krmila (mm)	800			800			800			8
Dolžina opore krmila (mm)	40			40			50			5
Dolžina gonilke (mm)	165			170			170			1
Velikost obročnikov	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F]

Vse navedene specifikacije se lahko spremenijo brez obvestila.