

TRANCE X ADVANCED E+ 1



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
CONTROLLER	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
BATTERY	EnergyPak Smart 625, EnergyPak Plus, 250Wh range extender compatible
FRAME	
SIZES	S, M, L, XL
COLORS	Panther Green
FRAME	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FORK	Fox 36 Live Valve, 150mm travel, 44mm offset, Grip2 damper, Boost 110x15QR, electronic adaptive suspension, e-bike integrated, e-bike integrated
SHOCK	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated
COMPONENTS	
HANDLEBAR	Giant Contact 35 Trail, 35x780mm
GRIPS	Giant Tactal Pro-E, single lock-on
STEM	Giant Contact SL 35
SEATPOST	Giant Contact Switch, dropper, 30,9mm (S:125, M:150, L/XL:170)
SADDLE	Giant Romero, Neutral
PEDALS	Flat pedal
DRIVETRAIN	
SHIFTERS	Shimano Deore XT
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano Deore XT, 12-speed, Shadow+
BRAKES	Shimano Deore, BR-M6120, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Shimano Deore, BL-MT6100
CASSETTE	Shimano HG-M6100, 10-51T, 12-speed
CHAIN	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor = 168, XS/S:160, M/L:165, XL:170)
BOTTOM BRACKET	-

WHEELS	
RIMS	Giant AM 29", Tubeless ready, 30mm inner width
HUBS	Shimano Deore XT, Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPOKES	Sapim E-Lite [r] Race [f]
TIRES	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO, 3c MaxxTerra[F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 120tpi 3C [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSORIES	
LIGHTING	Optional:- Giant Recon series e-bike lights available and direct connectable

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	425	450	475				
Seat Tube Angle	77,2° 78,0°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°				
Top Tube Length (mm)	577 575	607 605	637 635	667 665				
Head Tube Length (mm)	95	100	110	120				
Head Tube Angle	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°				
Fork Rake (mm)	44	44	44	44				
Trail (mm)	117 122,4	117 122,4	117 122,4	117 122,4				
Wheelbase (mm)	1220 1221	1239 1237	1268 1269	1300 1301				
Chain Stay Length (mm)	473 473	473 473	473 473	473 473				
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20				
Stack (mm)	606 601	611 605	621 614	630 624				
Reach (mm)	439 447	457 462	482 489	510 517				
Stand Over Height (mm)	740 746	727 734	718 726	715 723				
Handlebar Width (mm)	780	780	780	780				
Stem Length (mm)	40	40	50	50				
Crank Length (mm)	160	165	165	170				
Wheel Size	29"	29"	29"	29"				

All specifications listed are subject to change without notice.