

TRANCE X ADVANCED E+ 1



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
CONTROLLER	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED displayANT+ Wireless display compatible
BATTERY	EnergyPak Smart 625, EnergyPak Plus, 250Wh range extender compatible
ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	S, M, L, XL
ΧΡΩΜΑΤΑ	Panther Green
ΣΚΕΛΕΤΟΣ	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
ΠΙΠΟΥΝΙ	Fox 36 Live Valve, 150mm travel, 44mm offset, Grip2 damper, Boost 110x15QR, electronic adaptive suspension, e-bike integrated, e-bike integrated
ΑΝΑΡΤΗΣΗ	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact 35 Trail, 35x780mm
GRIPS	Giant Tactal Pro-E, single lock-on
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact SL 35
ΛΑΙΜΟΣ ΣΕΛΛΑΣ	Giant Contact Switch, dropper, 30,9mm (S:125, M:150, L/XL:170)
ΣΕΛΛΑ	Giant Romero, Neutral
ΠΕΝΤΑΛ	Flat pedal
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	Shimano Deore XT
ΝΤΕΡΑΓΙΕΡ ΕΜΠΡΟΣΘΙΟ	MRP HD2 co-moulded chain guide
ΝΤΕΡΑΓΙΕΡ ΟΠΙΣΘΙΟ.	Shimano Deore XT, 12-speed, Shadow+
ΦΡΕΝΑ	Shimano Deore, BR-M6120, 4-piston, hydraulic disc, 203mm
ΜΑΝΥΕΤΤΕΣ ΦΡΕΝΩΝ	Shimano Deore, BL-MT6100
CASETTE Ή ΕΛΕΥΘΕΡΟ	Shimano HG-M6100, 10-51T, 12-speed
ΑΛΥΣΙΔΑ	KMC e.12 Turbo, EcoProteq, e-bike optimized
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor = 168, XS/S:160, M/L:165, XL:170)
BOTTOM BRACKET	-

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant AM 29", Tubeless ready, 30mm inner width
ΚΕΝΤΡΑ	Shimano Deore XT, Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
ΑΚΤΙΝΕΣ	Sapim E-Lite [r] Race [f]
ΕΛΑΣΤΙΚΑ	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO, 3c MaxxTerra[F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 120tpi 3C [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSORIES	
LIGHTING	Optional:- Giant Recon series e-bike lights available and direct connectable

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	425	450	475
Seat Tube Angle	77,2° 78,0°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°
Top Tube Length (mm)	577 575	607 605	637 635	667 665
Head Tube Length (mm)	95	100	110	120
Head Tube Angle	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	117 122,4	117 122,4	117 122,4	117 122,4
Wheelbase (mm)	1220 1221	1239 1237	1268 1269	1300 1301
Chain Stay Length (mm)	473 473	473 473	473 473	473 473
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	611 605	621 614	630 624
Reach (mm)	439 447	457 462	482 489	510 517
Stand Over Height (mm)	740 746	727 734	718 726	715 723
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	50	50
Crank Length (mm)	160	165	165	170
Wheel Size	29"	29"	29"	29"

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση