

TRANCE X ADVANCED E+ 1



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATERÍA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONECTIVIDAD	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	S, M, L, XL
COLORES	Airglow/Carbon Smoke
CUADRO	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
TIJERA	Fox 36 Performance Elite Live Valve E-Tuned, 29er, 150mm travel, 44mm offset, Fit4 damper, Kabolt-X 110, electronic adaptive suspension, e-bike integrated
AMORTIGUADOR	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated, recommended sag: 30%
COMPONENTES	
MANUBRIO	Giant Contact SL 35, 35x780mm
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCIA	Giant Contact SL 35
POSTE DE ASIENTO	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
ASIENTO	Giant Romero, Neutral
PEDALES	Flat pedals
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore XT
DESVIADOR	MRP HD2 co-moulded chain guide
CAMBIO TRASERO	Shimano Deore XT, 12-speed, Shadow+
FRENOS	Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 220mm
PALANCAS DE FRENOS	Shimano Deore XT, I-spec EV
CASSETTE	Shimano CS-M7100, 10-51T, 12-speed
CADENA	KMC e.12 Turbo, EcoProteq, e-bike optimized
MULTIPLICACIÓN	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S:160mm, M/L: 165mm, XL:170mm)
EJE DE CENTRO	n/a

RUEDAS	
RUEDAS	e-TRX Hookless Clincher, 29", 30mm inner width
MAZAS	e-TRX 6 Bolt, Shimano Micro-spline, 110 x 15 [F], 148 x 12 [R] Thru Axle
NEUMÁTICOS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool) Inner tube supplied
ACCESORIOS	
LUCES	Optional:- Giant Recon series e-bike lights available and direct connectable
CANDADOS	Torx 25 Battery Lock with built-in Torque limiter

Precio: \$249,900.00

GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud de la Base del Poste de Asiento (mm)	400		425		450		475	
Ángulo de la Base del Poste de Asiento	77.2°	78.0°	76.0°	76.7°	76.0°	76.7°	76.0°	76.7°
Longitud del Tubo Superior (mm)	577	575	607	605	637	635	667	665
Longitud del Telescopio (mm)	95		100		110		120	
Ángulo del Telescopio	65.7°	66.5°	65.8°	66.5°	65.8°	66.5°	65.8°	66.5°
Rake (mm)	44		44		44		44	
Trail (mm)	117	122.4	117	122.4	117	122.4	117	122.4
Distancia entre Ejes (mm)	1220	1221	1239	1237	1268	1269	1300	1301
Longitud de Vaina Inferior (mm)	473	473	473	473	473	473	473	473
Caída del Eje de Centro (mm)	30	20	30	20	30	20	30	20
Stack (mm)	606	601	611	605	621	614	630	624
Reach (mm)	439	447	457	462	482	489	510	517
Altura del Tubo Superior al Suelo (mm)	740	746	727	734	718	726	715	723
Ancho del Manubrio (mm)	780		780		780		780	
Longitud de la Potencia (mm)	40		40		50		50	
Longitud de la Biela (mm)	160		165		165		170	
Tamaño de las Ruedas	29"		29"		29"		29"	

Todas las especificaciones están sujetas a cambios sin previo aviso.