

TRANCE X ADVANCED E+ 1

GIANT



TECHNIQUES

| TECHNOLOGIE HYBRID | |
|---------------------|---|
| MOTEUR | Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology |
| COMMANDE | Giant RideControl Ergo3, grip integrated remote |
| ECRAN | Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display |
| BATTERIE | Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible |
| CHARGEUR | Giant EnergyPak 6A smart charger, 60% in 2:15h |
| CONNECTIVITÉ | Giant RideControl App enabled ANT+ wireless display signal with e-bike profile |
| CADRE | |
| TAILLES | S, M, L, XL |
| COLORIS | Airglow/Carbon Smoke |
| CADRE | Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible |
| FOURCHE | Fox 36 Performance Elite Live Valve E-Tuned, 29er, 150mm travel, 44mm offset, Fit4 damper, Kabolt-X 110, electronic adaptive suspension, e-bike integrated |
| AMORTISSEUR | Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated, recommended sag: 30% |
| COMPOSANTS | |
| CINTRE | Giant Contact SL 35, 35x780mm |
| POIGNÉES | Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL) |
| POTENCE | Giant Contact SL 35 |
| TIGE DE SELLE | Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm) |
| SELLE | Giant Romero, Neutral |
| PÉDALES | Flat pedals |
| DÉRAILLEUR | |
| MANETTES | Shimano Deore XT |
| DÉRAILLEUR AVANT | MRP HD2 co-moulded chain guide |
| DÉRAILLEUR ARRIÈRE | Shimano Deore XT, 12-speed, Shadow+ |
| FREINS | Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 220mm |
| LEVIERS DE FREIN | Shimano Deore XT, I-spec EV |
| CASSETTE | Shimano CS-M7100, 10-51T, 12-speed |
| CHAÎNE | KMC e.12 Turbo, EcoProteq, e-bike optimized |
| PÉDALIER | Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S:160mm, M/L: 165mm, XL:170mm) |
| BOITIER DE PÉDALIER | n/a |

| ROUES | |
|--------------------------|--|
| JANTES | e-TRX Hookless Clincher, 29", 30mm inner width |
| MOYEURS | e-TRX 6 Bolt, Shimano Micro-spline, 110 x 15 [F], 148 x 12 [R] Thru Axle |
| PNEUS | Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F] Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R] |
| EXTRAS | Tubeless kit (liquid, valves, levers, manual, tool) Inner tube supplied |
| ACCESSOIRES | |
| ECLAIRAGE | Kit d'éclairage avant et arrière à piles |
| ANTI-VOL | Torx 25 Battery Lock with built-in Torque limiter |
| LIMITES | |
| POIDS TOTAL MAX AUTORISÉ | 156 kg (vélo, cycliste et bagages) |

Prix Public Conseillé: 7 200,00 €

GÉOMÉTRIE

| CADRE | S | | M | | L | | XL | |
|------------------------------------|---------------|---------------|---------------|---------------|---------------|------|-----|------|
| | LOW | HIGH | LOW | HIGH | LOW | HIGH | LOW | HIGH |
| Longueur de tube de selle (mm) | 400 | 425 | 450 | 475 | | | | |
| Angle de tube de selle | 77,2° 78,0° | 76,0° 76,7° | 76,0° 76,7° | 76,0° 76,7° | 76,0° 76,7° | | | |
| Longueur du tube supérieur (mm) | 577 575 | 607 605 | 637 635 | 667 665 | | | | |
| Longueur du tube de direction (mm) | 95 | 100 | 110 | 120 | | | | |
| Angle du tube de direction | 65,7° 66,5° | 65,8° 66,5° | 65,8° 66,5° | 65,8° 66,5° | 65,8° 66,5° | | | |
| Déport de fourche (mm) | 44 | 44 | 44 | 44 | | | | |
| Trail (mm) | 117 122,4 | 117 122,4 | 117 122,4 | 117 122,4 | | | | |
| Empattement (mm) | 1220 1221 | 1239 1237 | 1268 1269 | 1300 1301 | | | | |
| Longueur des bases (mm) | 473 473 | 473 473 | 473 473 | 473 473 | | | | |
| Drop du boîtier de pédalier (mm) | 30 20 | 30 20 | 30 20 | 30 20 | | | | |
| Stack (mm) | 606 601 | 611 605 | 621 614 | 630 624 | | | | |
| Reach (mm) | 439 447 | 457 462 | 482 489 | 510 517 | | | | |
| Hauteur en statique (mm) | 740 746 | 727 734 | 718 726 | 715 723 | | | | |
| Largeur de cintre (mm) | 780 | 780 | 780 | 780 | | | | |
| Longueur de potence (mm) | 40 | 40 | 50 | 50 | | | | |
| Longueur des manivelles (mm) | 160 | 165 | 165 | 170 | | | | |
| Diamètre des roues | 29" | 29" | 29" | 29" | | | | |

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.