

# TRANCE X ADVANCED E+ 1

**GIANT**

## SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
SENSOR	RideControl Ergo 3, grip integrated
PRIKAZ	RideControl GO, frame integrated LED displayANT+ Wireless display compatible
BATERIJA	EnergyPak Smart 625, EnergyPak Plus, 250Wh range extender compatible
OKVIR	
VELIČINE	S, M, L, XL
BOJE	Panther Green
OKVIR	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
VILICA	Fox 36 Live Valve, 150mm travel, 44mm offset, Grip2 damper, Boost 110x15QR, electronic adaptive suspension, e-bike integrated, e-bike integrated
AMORTIZER	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated
KOMPONENTE	
VOLAN	Giant Contact 35 Trail, 35x780mm
GRIPS	Giant Tactal Pro-E, single lock-on
LULA VOLANA	Giant Contact SL 35
CIJEV SJEDALA	Giant Contact Switch, dropper, 30,9mm (S:125, M:150, L/XL:170)
SJEDALO	Giant Romero, Neutral
PEDALE	Flat pedal
POGON	
RUČICE MJENJAČA	Shimano Deore XT
PREDNJI MJENJAČ	MRP HD2 co-moulded chain guide
STRAŽNJI MJENJAČ	Shimano Deore XT, 12-speed, Shadow+
KOČNICE	Shimano Deore, BR-M6120, 4-piston, hydraulic disc, 203mm
RUČICE KOČNICA	Shimano Deore, BL-MT6100
KAZETA	Shimano HG-M6100, 10-51T, 12-speed
LANAC	KMC e.12 Turbo, EcoProteq, e-bike optimized
POGON	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor = 168, XS/S:160, M/L:165, XL:170)
OSOVINA POGONA (BB)	-

KOTAČI	
OBRUČI	Giant AM 29", Tubeless ready, 30mm inner width
NABE	Shimano Deore XT, Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
ŽBICE	Sapim E-Lite [r] Race [f]
GUME	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO, 3c MaxxTerra[F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 120tpi 3C [R]
DODACI	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
DODACI	
SVJETLA	Optional:- Giant Recon series e-bike lights available and direct connectable

## GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dužina cijevi sjedala (mm)	400	425	450	475	500	525	550	575
Kut cijevi sjedala	77,2°	78,0°	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°
Dužina gornje cijevi (mm)	577	575	607	605	637	635	667	665
Dužina prednje cijevi (mm)	95	100	110	115	120	125	130	135
Kut vilice	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°	65,8°	66,5°
Zakrivljenost vilice (offset) (mm)	44	44	44	44	44	44	44	44
Staza (mm)	117	122,4	117	122,4	117	122,4	117	122,4
Međuosovinski razmak kotača (mm)	1220	1221	1239	1237	1268	1269	1297	1298
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	473	473	473	473	473	473	473	473
Položaj osovine pogona (mm)	30	20	30	20	30	20	30	20
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	606	601	611	605	621	614	631	624
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	439	447	457	462	482	489	507	514
Prekoračna visina (mm)	740	746	727	734	718	726	709	716
Širina volana (mm)	780	780	780	780	780	780	780	780
Dužina lule volana (mm)	40	40	50	50	50	50	50	50
Dužina poluge pedale (mm)	160	165	165	165	165	165	165	165
Veličina kotača	29"	29"	29"	29"	29"	29"	29"	29"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.