

TRANCE X ADVANCED E+ 1

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
BEDIENINGSUNIT	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
ACCU	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
LADER	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	S, M, L, XL
KLEUREN	Airglow/Carbon Smoke
FRAME	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
VOORVORK	Fox 36 Performance Elite Live Valve E-Tuned, 29er, 150mm travel, 44mm offset, Fit4 damper, Kabolt-X 110, electronic adaptive suspension, e-bike integrated
DEMPER	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated, recommended sag: 30%
ONDERDELEN	
STUUR	Giant Contact SL 35, 35x780mm
HANDVATTEN	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
STUURPEN	Giant Contact SL 35
ZADELPEN	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
ZADEL	Giant Romero, Neutral
PEDALEN	Flat pedals
AFMONTAGE	
SHIFTERS	Shimano Deore XT
VOORDERAILLEUR	MRP HD2 co-moulded chain guide
ACHTERDERAILLEUR	Shimano Deore XT, 12-speed, Shadow+
REMMEN	Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 220mm
REMHENDELS	Shimano Deore XT, I-spec EV
CASSETTE	Shimano CS-M7100, 10-51T, 12-speed
AANDRIJVING	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S:160mm, M/L: 165mm, XL:170mm)
BOTTOM BRACKET	n/a

WIELSET	
VELGEN	e-TRX Hookless Clincher, 29", 30mm inner width
NAVEN	e-TRX 6 Bolt, Shimano Micro-spline, 110 x 15 [F], 148 x 12 [R] Thru Axle
BANDEN	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRA'S	Tubeless kit (liquid, valves, levers, manual, tool) Inner tube supplied
ACCESSOIRES	
VERLICHTING	Optional:- Giant Recon series e-bike lights available and direct connectable
SLOT	Torx 25 Battery Lock with built-in Torque limiter

Adviesprijs: € 8.799,00

GEOMETRIE

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis lengte (mm)	400		425		450		475	
Zitbuis hoek	77,2°	78,0°	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°
Frame Lengte (horizontaal) (mm)	577	575	607	605	637	635	667	665
Balhoofdbuis Lengte (mm)	95		100		110		120	
Balhoofdbuis Hoek	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°	65,8°	66,5°
Vork Sprong (mm)	44		44		44		44	
Naloop (mm)	117	122,4	117	122,4	117	122,4	117	122,4
Wielbasis (mm)	1220	1221	1239	1237	1268	1269	1300	1301
Liggende achtervork lengte (mm)	473	473	473	473	473	473	473	473
Bottom Bracket Drop (mm)	30	20	30	20	30	20	30	20
Stack (mm)	606	601	611	605	621	614	630	624
Reach (mm)	439	447	457	462	482	489	510	517
Stand Over Height (mm)	740	746	727	734	718	726	715	723
Stuur breedte (mm)	780		780		780		780	
Stuurpen Lengte (mm)	40		40		50		50	
Cranklengte (mm)	160		165		165		170	
Wielmaat	29"		29"		29"		29"	

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.