



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
SENSOR	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED displayANT+ Wireless display compatible
BATTERY	EnergyPak Smart 625, EnergyPak Plus, 250Wh range extender compatible
CADRU	
MARIMI	S, M, L, XL
CULORI	Panther Green
CADRU	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FURCA	Fox 36 Live Valve, 150mm travel, 44mm offset, Grip2 damper, Boost 110x15QR, electronic adaptive suspension, e-bike integrated, e-bike integrated
SOC	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated
COMPONENTE	
GHIDON	Giant Contact 35 Trail, 35x780mm
GRIPS	Giant Tactal Pro-E, single lock-on
PIPA	Giant Contact SL 35
TIJA SA	Giant Contact Switch, dropper, 30,9mm (S:125, M:150, L/XL:170)
SA	Giant Romero, Neutral
PEDALE	Flat pedal
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano Deore XT
SCHIMBATOR FATA	MRP HD2 co-moulded chain guide
SCHIMBATOR SPATE	Shimano Deore XT, 12-speed, Shadow+
FRANE	Shimano Deore, BR-M6120, 4-piston, hydraulic disc, 203mm
MANETE FRANA	Shimano Deore, BL-MT6100
PINIOANE	Shimano HG-M6100, 10-51T, 12-speed
LANT	KMC e.12 Turbo, EcoProteq, e-bike optimized
ANGRENAJ	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor = 168, XS/S:160, M/L:165, XL:170)
BOTTOM BRACKET	-

ROTI	
JANTE	Giant AM 29", Tubeless ready, 30mm inner width
BUTUCI	Shimano Deore XT, Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPITE	Sapim E-Lite [r] Race [f]
ANVELOPE	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO, 3c MaxxTerra[F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 120tpi 3C [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSORIES	
LIGHTING	Optional:- Giant Recon series e-bike lights available and direct connectable

GEOMETRIE

CADRU	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	425	450	475
Seat Tube Angle	77,2° 78,0°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°
Top Tube Length (mm)	577 575	607 605	637 635	667 665
Head Tube Length (mm)	95	100	110	120
Head Tube Angle	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	117 122,4	117 122,4	117 122,4	117 122,4
Wheelbase (mm)	1220 1221	1239 1237	1268 1269	1300 1301
Chain Stay Length (mm)	473 473	473 473	473 473	473 473
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	611 605	621 614	630 624
Reach (mm)	439 447	457 462	482 489	510 517
Stand Over Height (mm)	740 746	727 734	718 726	715 723
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	50	50
Crank Length (mm)	160	165	165	170
Wheel Size	29"	29"	29"	29"

Toate specificatiile enumerate se pot schimba fara notificare prealabila.