

TRANCE X ADVANCED E+ 1

GIANT



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
TIPALO	Giant RideControl Ergo3, grip integrated remote
PRIKAZOVALNIK	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATERIJA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Airglow/Carbon Smoke
OKVIR	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
VILICE	Fox 36 Performance Elite Live Valve E-Tuned, 29er, 150mm travel, 44mm offset, Fit4 damper, Kabolt-X 110, electronic adaptive suspension, e-bike integrated
AMORTIZER	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated, recommended sag: 30%
KOMPONENTE	
KRMILO	Giant Contact SL 35, 35x780mm
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28–30mm (S/M) 142mm Ø29–32mm (L/XL)
OPORA KRMILA	Giant Contact SL 35
OPORA SEDEŽA	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SEDEŽ	Giant Romero, Neutral
PEDALA	Flat pedals
POGON	
PRESTAVNE ROČICE	Shimano Deore XT
PREDNJI MENJALNIK	MRP HD2 co-moulded chain guide
ZADNJI MENJALNIK	Shimano Deore XT, 12-speed, Shadow+
ZAVORE	Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 220mm
ZAVORNE ROČICE	Shimano Deore XT, I-spec EV
VERIŽNIK	Shimano CS-M7100, 10-51T, 12-speed
VERIGA	KMC e.12 Turbo, EcoProteq, e-bike optimized
GONILKE Z VERIŽNIKI	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S:160mm, M/L: 165mm, XL:170mm)
BOTTOM BRACKET	n/a

OBROČNIKI	
OBROČI	e-TRX Hookless Clincher, 29", 30mm inner width
PESTA	e-TRX 6 Bolt, Shimano Micro-spline, 110 x 15 [F], 148 x 12 [R] Thru Axle
PLAŠČI	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
DODATKI	Tubeless kit (liquid, valves, levers, manual, tool) Inner tube supplied
DODATNA OPREMA	
SVETILA	Optional:- Giant Recon series e-bike lights available and direct connectable
KLJUČAVNICA	Torx 25 Battery Lock with built-in Torque limiter

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	400		425		450		475	
Kot sedežne cevi	77,2°	78,0°	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°
Top Tube Length (mm)	577	575	607	605	637	635	667	665
Višina glave okvirja (mm)	95		100		110		120	
Krmilni kot	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°	65,8°	66,5°
Zamik vpetja osi (mm)	44		44		44		44	
Trail (mm)	117	122,4	117	122,4	117	122,4	117	122,4
Medosna razdalja (mm)	1220	1221	1239	1237	1268	1269	1300	1301
Dolžina cevi ob verigi (mm)	473	473	473	473	473	473	473	473
Bottom Bracket Drop (mm)	30	20	30	20	30	20	30	20
Oddaljenost zgornje cevi od gonilne osi (mm)	606	601	611	605	621	614	630	624
Doseg (mm)	439	447	457	462	482	489	510	517
Višina zgornje cevi (mm)	740	746	727	734	718	726	715	723
Širina krmila (mm)	780		780		780		780	
Dolžina opore krmila (mm)	40		40		50		50	
Dolžina gonilke (mm)	160		165		165		170	
Velikost obročnikov	29"		29"		29"		29"	

Vse navedene specifikacije se lahko spremenijo brez obvestila.