

TRANCE X ADVANCED E+ 2

GIANT



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATERÍA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONECTIVIDAD	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	S, M, L, XL
COLORES	Gloss Carbon Smoke/ Matte Carbon Smoke
CUADRO	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
TIJERA	Fox 36 Float Performance E-Tuned, 29er, 150mm travel, 44mm offset, Grip 3-position Micro Adjust damper, Kabolt-X 110
AMORTIGUADOR	Fox DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPONENTES	
MANUBRIO	Giant Contact 35 Trail, 35x780mm
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCIA	Giant Contact SL 35
POSTE DE ASIENTO	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
ASIENTO	Giant Romero, Neutral
PEDALES	Flatpedal
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore SLX
DESVIADOR	MRP HD2 co-moulded chain guide
CAMBIO TRASERO	Shimano Deore SLX, 12-speed, Shadow+
FRENOS	Shimano SLX, BR-M7120, 4-piston, hydraulic disc, 203mm
PALANCAS DE FRENOS	Shimano SLX, 1-spec EV
CASSETTE	Shimano CS-M6100, 10-51T, 12-speed
CADENA	KMC e.12 Sport, NP/NP, e-bike optimized
MULTIPLICACIÓN	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S:160mm, M/L: 165mm, XL:170mm)
EJE DE CENTRO	n/a

RUEDAS	
RUEDAS	Giant AM30, Tubeless ready, 30mm inner width, 29"
MAZAS	Shimano MT410, Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAYOS	Sapim E-Lite [R] Race [F], e-bike optimized
NEUMÁTICOS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESORIOS	
LUCES	Optional:- Giant Recon series e-bike lights available and direct connectable
CANDADOS	Torx 25 Battery Lock with built-in Torque limiter

Precio: \$189,900.00

GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud de la Base del Poste de Asiento (mm)	400	425	450	475				
Ángulo de la Base del Poste de Asiento	77.2° 78.0°	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°		
Longitud del Tubo Superior (mm)	577 575	607 605	637 635	667 665				
Longitud del Telescopio (mm)	95	100	110	120				
Ángulo del Telescopio	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°		
Rake (mm)	44	44	44	44				
Trail (mm)	117 122.4	117 122.4	117 122.4	117 122.4	117 122.4	117 122.4		
Distancia entre Ejes (mm)	1220 1221	1239 1237	1268 1269	1300 1301				
Longitud de Vaina Inferior (mm)	473 473	473 473	473 473	473 473				
Caída del Eje de Centro (mm)	30 20	30 20	30 20	30 20				
Stack (mm)	606 601	611 605	621 614	630 624				
Reach (mm)	439 447	457 462	482 489	510 517				
Altura del Tubo Superior al Suelo (mm)	740 746	727 734	718 726	715 723				
Ancho del Manubrio (mm)	780	780	780	780				
Longitud de la Potencia (mm)	40	40	50	50				
Longitud de la Biela (mm)	160	165	165	170				
Tamaño de las Ruedas	29"	29"	29"	29"				

Todas las especificaciones están sujetas a cambios sin previo aviso.