

TRANCE X ADVANCED E+ 2

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRU	
MARIMI	S, M, L, XL
CULORI	Gloss Carbon Smoke/ Matte Carbon Smoke
CADRU	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
FURCA	Fox 36 Float Performance E-Tuned, 29er, 150mm travel, 44mm offset, Grip 3-position Micro Adjust damper, Kabolt-X 110
SOC	Fox DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPONENTE	
GHIDON	Giant Contact 35 Trail, 35x780mm
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
PIPA	Giant Contact SL 35
TIJA SA	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SA	Giant Romero, Neutral
PEDALE	Flatpedal
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano Deore SLX
SCHIMBATOR FATA	MRP HD2 co-moulded chain guide
SCHIMBATOR SPATE	Shimano Deore SLX, 12-speed, Shadow+
FRANE	Shimano SLX, BR-M7120, 4-piston, hydraulic disc, 203mm
MANETE FRANA	Shimano SLX, I-spec EV
PINIOANE	Shimano CS-M6100, 10-51T, 12-speed
LANT	KMC e.12 Sport, NP/NP, e-bike optimized
ANGRENAJ	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S:160mm, M/L: 165mm, XL:170mm)
BOTTOM BRACKET	n/a

ROTI	
JANTE	Giant AM30, Tubeless ready, 30mm inner width, 29"
BUTUCI	Shimano MT410, Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPITE	Sapim E-Lite [R] Race [F], e-bike optimized
ANVELOPE	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSORIES	
LIGHTING	Optional:- Giant Recon series e-bike lights available and direct connectable
LOCK	Torx 25 Battery Lock with built-in Torque limiter

GEOMETRIE

CADRU	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400		425		450		475	
Seat Tube Angle	77,2°	78,0°	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°
Top Tube Length (mm)	577	575	607	605	637	635	667	665
Head Tube Length (mm)	95		100		110		120	
Head Tube Angle	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°	65,8°	66,5°
Fork Rake (mm)	44		44		44		44	
Trail (mm)	117	122,4	117	122,4	117	122,4	117	122,4
Wheelbase (mm)	1220	1221	1239	1237	1268	1269	1300	1301
Chain Stay Length (mm)	473	473	473	473	473	473	473	473
Bottom Bracket Drop (mm)	30	20	30	20	30	20	30	20
Stack (mm)	606	601	611	605	621	614	630	624
Reach (mm)	439	447	457	462	482	489	510	517
Stand Over Height (mm)	740	746	727	734	718	726	715	723
Handlebar Width (mm)	780		780		780		780	
Stem Length (mm)	40		40		50		50	
Crank Length (mm)	160		165		165		170	
Wheel Size	29"		29"		29"		29"	

Toate specificatiile enumerate se pot schimba fara notificare prealabila.