

TRANCE X ADVANCED E+ ELITE 0

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 Mg, 85Nm, PedalPlus 6-Sensor technology
CONTROLLER	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED consoleOptional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
FRAME	
SIZES	S, M, L, XL
COLORS	Blue Dragonfly
FRAME	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FORK	Fox 36 Factory E-Tuned, 29er, 150mm travel, 44mm offset, Grip2 VVC damper, Kabolt-X 110
SHOCK	Fox Float X Factory, EVOL, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPONENTS	
HANDLEBAR	Giant Contact SLR Trail, carbon, 800mm
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28–30mm (S/M) 142mm Ø29–32mm (L/XL)
STEM	Giant Contact SLR Trail, integrated,40/45/50mm Reach, 7/9degree Sweep Adjust System
SEATPOST	Fox Transfer Factory (S:125, M:150, L: 175, XL:200mm) Fox MMX Remote
SADDLE	Giant Romero SL, Neutral
PEDALS	n/a
DRIVETRAIN	
SHIFTERS	SRAM AXS Rocker Paddle, wireless electronic shifting
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	SRAM XX Eagle Transmission, AXS
BRAKES	SRAM G2 Ultimate, 4-piston, hydraulic disc, 200mm[F], 180mm[R]
BRAKE LEVERS	SRAM Code RSC
CASSETTE	SRAM XX Eagle SL Transmission, 10-52T, 12-speed
CHAIN	SRAM XX Eagle Transmission, Powerlink
CRANKSET	SRAM Eagle Transmission chain ring 36T 104BCDPraxis Carbon e-crank arms (S:160, M/L:165, XL:170) Q-factor=168mm, Chainline: 55mm, Max Chainring: 38T
BOTTOM BRACKET	n/a

WHEELS	
RIMS	Zipp 3MOTO 29" [F] /27.5" [R], Carbon
HUBS	Zipp 3MOTO ZM2
SPOKES	Zipp 3MOTO
TIRES	Maxxis Dissector 29X2.40" Foldable, TLR, EXO [F]Maxxis Rekon 27.5x2.4" Foldable, TLR, EXO+ [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool) and inner tube for GA/NZOnly sealant and levers for other countries.
ACCESSORIES	
LIGHTING	Optional:- Giant Recon series e-bike lights available and direct connectable

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	425	450	475				
Seat Post Insertion Depth (mm)	220	245	270	295				
Seat Tube Angle	77,2° 78,0°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°				
Top Tube Length (mm)	577 575	607 605	636 634	665 663				
Head Tube Length (mm)	95	100	115	130				
Head Tube Angle	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°				
Fork Rake (mm)	44	44	44	44				
Trail (mm)	113,1 108	113,1 108	113,1 108	113,1 108				
Wheelbase (mm)	1194 1195	1215 1212	1244 1244	1275 1275				
Chain Stay Length (mm)	447 447	447 447	447 447	447 447				
Bottom Bracket Drop (mm)	10	10	10	10				
Stack (mm)	607 601	611 605	625 619	639 633				
Reach (mm)	439 447	457 462	480 487	505 513				
Stand Over Height (mm)	726 735	733 742	732 741	741 750				
Handlebar Width (mm)	780	780	780	780				
Stem Length (mm)	40	40	50	50				
Crank Length (mm)	160	165	165	170				
Wheel Size	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]				

All specifications listed are subject to change without notice.