

TRANCE X ADVANCED E+ ELITE 1

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
CONTROLLER	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
BATTERY	EnergyPak Smart 400Wh EnergyPak Plus, range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S, M, L, XL
COLOURS	Gunmetal Black/Black
FRAME	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FORK	Fox 36 Performance Elite Live Valve, 150mm travel, 44mm offset, Grip2 damper, Boost 110x15QR, electronic adaptive suspension, e-bike integrated
SHOCK	Fox Float X Factory, EVOL, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPONENTS	
HANDLEBAR	Giant Contact SLR Trail, carbon
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28–30mm (S/M) 142mm Ø29–32mm (L/XL)
STEM	Giant Contact SLR Trail
SEATPOST	Tranz-X Rad+ travel adjust dropper
SADDLE	Giant Romero, Neutral
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Rocker Paddle, wireless electronic shifting
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	SRAM GX Eagle AXS
BRAKES	SRAM Code R, hydraulic disc, 220mm[F] / 200mm[R]
BRAKE LEVERS	SRAM Code R
CASSETTE	SRAM XG-1275, 10-52T, 12-speed
CHAIN	SRAM GX Eagle PowerLock
CRANKSET	Praxis Performance Carbon e-crank arms SRAM X-SYNC Eagle 36T chain ring
BOTTOM BRACKET	N/A

WHEELS	
RIMS	E-TRX Hookless Tubeless ready Carbon 29 [F] / 27.5 [R] 30mm inner width
HUBS	E-TRX MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 SRAM XD Drive Body Pawl Driver (Pawl 36x2 T) Thru-axle [R]
TIRES	Maxxis Minion DHF 29x2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers)
ACCESSORIES	
LIGHTING	Optional- Giant Recon series e-bike lights available and direct connectable
CARRIER	-

Price: \$14,499.00

GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	425	450	475
Seat Tube Angle	77.2° 78.0°	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°
Top Tube Length (mm)	577 575	607 605	636 634	665 663
Head Tube Length (mm)	95	100	115	130
Head Tube Angle	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	113.1 108	113.1 108	113.1 108	113.1 108
Wheelbase (mm)	1194 1195	1215 1212	1244 1244	1275 1275
Chain Stay Length (mm)	447 447	447 447	447 447	447 447
Bottom Bracket Drop (mm)	10	10	10	10
Stack (mm)	607 601	611 605	625 619	639 633
Reach (mm)	439 447	457 462	480 487	505 513
Stand Over Height (mm)	726 735	733 742	732 741	741 750
Stem Length (mm)	40	40	50	50
Crank Length (mm)	160	165	165	170
Wheel Size	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.