

TRANCE X ADVANCED E+ ELITE 1



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 Magnesium 85Nm, PedalPlus 6-Sensor technology
CONTROLLER	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
BATTERY	EnergyPak Smart 400Wh EnergyPak Plus, range extender compatible
FRAME	
SIZES	S, M, L, XL
COLOURS	Raw Carbon
FRAME	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, flip chip, UDH hanger 12x148mm thru-axle
FORK	Fox 36 Factory E-Tuned, 29er, 150mm travel, 44mm offset, Grip2 VVC damper, Kabolt-X 110
SHOCK	Fox Float X Factory, EVOL Large Volume sleeve, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact SLR Integrated, composite, 35mm
GRIPS	Giant Tactal Pro-E, single lock-on
STEM	Giant Contact SLR Trail, integrated, 40/45/50mm Reach, 7/9degree Sweep Adjust System
SEATPOST	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 559mm XL: 170-200mm travel / 30.9 x 559mm
SADDLE	Giant Romero
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	SRAM GX Eagle T-Type AXS
BRAKES	SRAM Code R, 4-piston hydraulic disc, 220mm[F], 200mm[R]
BRAKE LEVERS	SRAM Code R
CASSETTE	SRAM GX, T-Type 10x52, 12-speed
CHAIN	SRAM GX T-Type
CRANKSET	Praxis Performance Carbon e-crank arms SRAM Eagle T-Type steel 36T chain ring S:160mm, M: 160mm, L:165mm, XL:165mm
BOTTOM BRACKET	N/A

WHEELS	
RIMS	E-TRX Hookless Tubeless ready Carbon 29 [F] / 27.5 [R] 30mm inner width
HUBS	E-TRX MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 SRAM XD Drive Body Pawl Driver (Pawl 36x2 T) Thru-axle [R]
SPOKES	Sapim E-Lite [R] Race [F], e-bike optimised
TIRES	Maxxis Minion DHF 29x2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers)
ACCESSORIES	
LIGHTING	Optional- Giant Recon series e-bike lights available and direct connectable

Price: \$14,999.00

GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	220	245	270	295
Seat Tube Angle	77.2° 78.0°	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°
Top Tube Length (mm)	577 575	607 605	636 634	665 663
Head Tube Length (mm)	95	100	115	130
Head Tube Angle	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	113.1 108	113.1 108	113.1 108	113.1 108
Wheelbase (mm)	1194 1195	1215 1212	1244 1244	1275 1275
Chain Stay Length (mm)	447 447	447 447	447 447	447 447
Bottom Bracket Drop (mm)	10	10	10	10
Stack (mm)	607 601	611 605	625 619	639 633
Reach (mm)	439 447	457 462	480 487	505 513
Stand Over Height (mm)	726 735	733 742	732 741	741 750
Stem Length (mm)	40	40	50	50
Crank Length (mm)	160	165	165	170
Wheel Size	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.