

# TRANCE X ADVANCED E+ ELITE 1

GIANT



## ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	Giant SyncDrive Pro2 Magnesium 85Nm, PedalPlus 6-Sensor technology
MANDO	Giant RideControl Ergo3, grip integrated remote
PANTALLA	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATERÍA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CARGADOR	Giant EnergyPak 4A smart charger, 60% in 1:45
CONECTIVIDAD	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	S, M, L, XL
COLORES	Gunmetal Black/Black
CUADRO	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system, patilla de cambio UDH
HORQUILLA	Fox 36 Factory E-Tuned, 29er, 150mm travel, 44mm offset, Grip2 VVC damper, Kabolt-X 110
AMORTIGUADOR	Fox Float X Factory, EVOL, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPONENTES	
MANILLAR	Giant Contact SLR Trail, carbon, 800mm
PUÑOS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCIA	Giant Contact SLR Trail, integrated, 40/45/50mm Reach, 7/9degree Sweep Adjust System
TIJA DE SILLÍN	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SILLÍN	Giant Romero, Neutral
PEDALES	n/a
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS Rocker Paddle, wireless electronic shifting
DESVIADOR	MRP HD2 co-moulded chain guide
CAMBIO TRASERO	SRAM GX Eagle AXS
FRENOS	SRAM Code R, hydraulic disc, 220mm[F] / 200mm[R]
PALANCAS DE FRENOS	SRAM Code R
CASETTE	SRAM XG-1275, 10-52T, 12-speed
CADENA	SRAM GX Eagle PowerLock
JGO. PLATOS Y BIELAS	Praxis Carbon e-crank arms (S/M:160, L/XL:165) SRAM Eagle Transmission E-MTB Chainring, Steel 36T
CAJA DE PEDALIER	n/a

RUEDAS	
LLANTAS	TRX 2 Carbon Hookless Clincher, 29" [F] / 27.5" [R], 30mm inner width
BUJES	E-TRX MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 SRAM XD Drive Body Pawl Driver (Pawl 36x2 T) Thru-axle [R]
CUBIERTAS	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESORIOS	
LUCES	Optional:- Giant Recon series e-bike lights available and direct connectable
PORTA-EQUIPAJES	-

Precio: 9.499,00 €

## GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud del tubo del sillín (mm)	400	425	450	475				
Ángulo del tubo del sillín	77,2°   78,0°	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°			
Longitud del tubo superior (mm) (mm)	577   575	607   605	636   634	665   663				
Longitud del tubo de dirección (mm) (mm)	95	100	115	130				
Ángulo del tubo de dirección	65,7°   66,5°	65,8°   66,5°	65,8°   66,5°	65,8°   66,5°				
Inclinación de la horquilla (mm)	44	44	44	44				
Trail (mm) (mm)	113,1   108	113,1   108	113,1   108	113,1   108				
Distancia entre ejes (mm) (mm)	1194   1195	1215   1212	1244   1244	1275   1275				
Longitud de la vaina (mm) (mm)	447   447	447   447	447   447	447   447				
Caída del eje de pedalier (mm) (mm)	10	10	10	10				
Stack (mm) (mm)	607   601	611   605	625   619	639   633				
Reach (mm) (mm)	439   447	457   462	480   487	505   513				
Altura del suelo al tubo (mm) (mm)	726   735	733   742	732   741	741   750				
Ancho del manillar (mm) (mm)	780	780	780	780				
Longitud de la potencia (mm) (mm)	40	40	50	50				
Longitud de las bielas (mm) (mm)	160	165	165	170				
Tamaño de ruedas	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F				

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.