

TRANCE X ADVANCED E+ ELITE 1

GIANT



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 Mg, 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED consoleOptional wireless ANT+ display
BATERÍA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CUADRO	
TALLAS	S, M, L, XL
COLORES	Raw Carbon
CUADRO	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
TIJERA	Fox 36 Factory E-Tuned, 29er, 150mm travel, 44mm offset, Grip2 VVC damper, Kabolt-X 110
AMORTIGUADOR	Fox Float X Factory, EVOL, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPONENTES	
MANUBRIO	Giant Contact SLR Trail, carbon, 800mm
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCIA	Giant Contact SLR Trail, integrated,40/45/50mm Reach, 7/9degree Sweep Adjust System
POSTE DE ASIENTO	Tranz-X Rad+ 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
ASIENTO	Giant Romero
PEDALES	n/a
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS Rocker Paddle, wireless electronic shifting
DESVIADOR	MRP HD2 co-moulded chain guide
CAMBIO TRASERO	SRAM GX Eagle Transmission, AXS
FRENOS	SRAM Code R, 4-piston hydraulic disc, 220mm[F], 200mm[R]
PALANCAS DE FRENOS	SRAM Code R
CASSETTE	SRAM GX Eagle Transmission, 10-52T, 12-speed
CADENA	SRAM GX Eagle Transmission Flattop Chain, Powerlock
MULTIPLICACIÓN	SRAM Eagle Transmission chain ring 36T 104BCDPraxis Carbon e-crank arms (S:160, M/L:165, XL:170) Q-factor=168mm, Chainline: 55mm, Max Chainring: 38T
EJE DE CENTRO	n/a

RUEDAS	
RUEDAS	Giant TRX Carbon, 30mm inner width, Wide Side Wall Design for improved strength and flat protection
MAZAS	Giant TRX, E-Drive 260Nm 6-Pawl Driver, 72T engagement, MicroSpline body, 110 x 15 [F], 148 x 12 [R] Thru-axle, e-bike optimized
RAYOS	Sapim E-Lite [R] Race [F], e-bike optimized
NEUMÁTICOS	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESORIOS	
LUCES	Optional:- Giant Recon series e-bike lights available and direct connectable

Precio: \$199,990.00

GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud de la Base del Poste de Asiento (mm)	400		425		450		475	
Seat Post Insertion Depth (mm)	220		245		270		295	
Ángulo de la Base del Poste de Asiento	77.2°	78.0°	76.0°	76.7°	76.0°	76.7°	76.0°	76.7°
Longitud del Tubo Superior (mm)	577	575	607	605	636	634	665	663
Longitud del Telescopio (mm)	95		100		115		130	
Ángulo del Telescopio	65.7°	66.5°	65.8°	66.5°	65.8°	66.5°	65.8°	66.5°
Rake (mm)	44		44		44		44	
Trail (mm)	113.1	108	113.1	108	113.1	108	113.1	108
Distancia entre Ejes (mm)	1194	1195	1215	1212	1244	1244	1275	1275
Longitud de Vaina Inferior (mm)	447	447	447	447	447	447	447	447
Caída del Eje de Centro (mm)	10		10		10		10	
Stack (mm)	607	601	611	605	625	619	639	633
Reach (mm)	439	447	457	462	480	487	505	513
Altura del Tubo Superior al Suelo (mm)	726	735	733	742	732	741	741	750
Ancho del Manubrio (mm)	780		780		780		780	
Longitud de la Potencia (mm)	40		40		50		50	
Longitud de la Biela (mm)	160		165		165		170	
Tamaño de las Ruedas	29" [F] 27.5" [R]		29" [F] 27.5" [R]		29" [F] 27.5" [R]		29" [F] 27.5" [R]	

Todas las especificaciones están sujetas a cambios sin previo aviso.