

TRANCE X ADVANCED E+ ELITE 1

GIANT

CARACTÉRISTIQUES TECHNIQUES

TECHNOLOGIE HYBRID	
MOTOR	Giant SyncDrive Pro2 Magnesium 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATTERIE	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRE	
TAILLES	S, M, L, XL
COLORIS	Gunmetal Black/Black
CADRE	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FOURCHE	Fox 36 Factory E-Tuned, 29er, 150mm travel, 44mm offset, Grip2 VVC damper, Kabolt-X 110
AMORTISSEUR	Fox Float X Factory, EVOL, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPOSANTS	
CINTRE	Giant Contact SLR Trail, carbon, 800mm
POIGNÉES	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCE	Giant Contact SLR Trail, integrated, 40/45/50mm Reach, 7/9degree Sweep Adjust System
TIGE DE SELLE	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SELLE	Giant Romero, Neutral
PÉDALES	n/a
DÉRAILLEUR	
MANETTES DÉRAILLEUR	SRAM AXS Rocker Paddle, wireless electronic shifting
DÉRAILLEUR AVANT	MRP HD2 co-moulded chain guide
DÉRAILLEUR ARRIÈRE	SRAM GX Eagle AXS
FREINS	SRAM Code R, hydraulic disc, 220mm[F]/200mm[R]
LEVIERS DE FREIN	SRAM Code R
CASSETTE	SRAM XG-1275, 10-52T, 12-speed
CHAÎNE	SRAM GX Eagle PowerLock
PÉDALIER	Praxis Carbon e-crank arms (S/M:160, L/XL:165) SRAM Eagle Transmission E-MTB Chainring, Steel 36T
PÉDALIER	n/a

ROUES	
JANTES	E-TRX Hookless Tubeless ready Carbon 29 [F] / 27.5 [R] 30mm inner width
MOYEURS	E-TRX MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 SRAM XD Drive Body Pawl Driver (Pawl 36x2 T) Thru-axle [R]
PNEUS	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSOIRES	
ÉCLAIRAGE	Optional- Giant Recon series e-bike lights available and direct connectable
CARRIER	-

GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	400	425	450	475				
Angle de tube de selle	77,2° 78,0°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°			
Longueur du tube supérieur (mm)	577 575	607 605	636 634	665 663				
Longueur du tube de direction (mm)	95	100	115	130				
Angle du tube de direction	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°				
Déport de fourche (mm)	44	44	44	44				
Chasse (mm)	113,1 108	113,1 108	113,1 108	113,1 108				
Empattement (mm)	1194 1195	1215 1212	1244 1244	1275 1275				
Longueur des bases (mm)	447 447	447 447	447 447	447 447				
Hauteur du boîtier de pédalier (mm)	10	10	10	10				
Stack (mm)	607 601	611 605	625 619	639 633				
Reach (mm)	439 447	457 462	480 487	505 513				
Hauteur d'enjambement (mm)	726 735	733 742	732 741	741 750				
Largeur de cintre (mm)	780	780	780	780				
Longueur de potence (mm)	40	40	50	50				
Longueur des manivelles (mm)	160	165	165	170				
Diamètre des roues	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F				

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.