

TRANCE X ADVANCED E+ ELITE 1

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 Mg, 85Nm, PedalPlus 6-Sensor technology
BEDIENINGSUNIT	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED consoleOptional wireless ANT+ display
ACCU	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
FRAME	
MATEN	S, M, L, XL
KLEUREN	Raw Carbon
FRAME	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
VOORVORK	Fox 36 Factory E-Tuned, 29er, 150mm travel, 44mm offset, Grip2 VVC damper, Kabolt-X 110
DEMPER	Fox Float X Factory, EVOL, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
ONDERDELEN	
STUUR	Giant Contact SLR Trail, carbon, 800mm
HANDVATTEN	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
STUURPEN	Giant Contact SLR Trail, integrated,40/45/50mm Reach, 7/9degree Sweep Adjust System
ZADELPEN	Tranz-X Rad+ 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
ZADEL	Giant Romero
PEDALEN	n/a
AFMONTAGE	
SHIFTERS	SRAM AXS Rocker Paddle, wireless electronic shifting
VOORDERAILLEUR	MRP HD2 co-moulded chain guide
ACHTTERDERAILLEUR	SRAM GX Eagle Transmission, AXS
REMMEN	SRAM Code R, 4-piston hydraulic disc, 220mm[F], 200mm[R]
REMHENDELS	SRAM Code R
CASSETTE	SRAM GX Eagle Transmission, 10-52T, 12-speed
AANDRIJVING	SRAM GX Eagle Transmission Flattop Chain, Powerlock
CRANKSET	SRAM Eagle Transmission chain ring 36T 104BCDPraxis Carbon e-crank arms (S:160, M/L:165, XL:170) Q-factor=168mm, Chainline: 55mm, Max Chainring: 38T
BOTTOM BRACKET	n/a

WIELSET	
VELGEN	Giant TRX Carbon, 30mm inner width, Wide Side Wall Design for improved strength and flat protection
NAVEN	Giant TRX, E-Drive 260Nm 6-Pawl Driver, 72T engagement, MicroSpline body, 110 x 15 [F], 148 x 12 [R] Thru-axle, e-bike optimized
SPAKEN	Sapim E-Lite [R] Race [F], e-bike optimized
BANDEN	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRA'S	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSOIRES	
VERLICHTING	Optional:- Giant Recon series e-bike lights available and direct connectable

Adviesprijs: € 9.999,00

GEOMETRIE

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Zitbuis lengte (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	220	245	270	295
Zitbuis hoek	77,2° 78,0°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°
Frame Lengte (horizontaal) (mm)	577 575	607 605	636 634	665 663
Balhoofdbuis Lengte (mm)	95	100	115	130
Balhoofdbuis Hoek	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	113,1 108	113,1 108	113,1 108	113,1 108
Wielbasis (mm)	1194 1195	1215 1212	1244 1244	1275 1275
Liggende achtervork lengte (mm)	447 447	447 447	447 447	447 447
Bottom Bracket Drop (mm)	10	10	10	10
Stack (mm)	607 601	611 605	625 619	639 633
Reach (mm)	439 447	457 462	480 487	505 513
Stand Over Height (mm)	726 735	733 742	732 741	741 750
Stuur breedte (mm)	780	780	780	780
Stuurpen Lengte (mm)	40	40	50	50
Cranklengte (mm)	160	165	165	170
Wielmaat	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.