

TRANCE X ADVANCED E+ ELITE 2



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 Magnesium 85Nm, PedalPlus 6-Sensor technology
CONTROLLER	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S, M, L, XL
COLORS	Amber Glow/Cordovan
FRAME	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FORK	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip 3-position Micro Adjust damper, Boost 110x15QR
SHOCK	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPONENTS	
HANDLEBAR	Giant Contact SL 35 Trail, 35x780mm
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
STEM	Giant Contact SL 35
SEATPOST	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SADDLE	Giant Romero, Neutral
PEDALS	n/a
DRIVETRAIN	
SHIFTERS	Shimano SLX
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano SLX, 12-speed, Shadow+
BRAKES	Shimano SLX, BR-M7120, 4-piston, hydraulic disc, 203mm [F/R]
BRAKE LEVERS	Shimano SLX, I-spec EV
CASSETTE	Shimano, CS-M6100, 10-51T, 12-speed
CHAIN	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, S:160, M/L:165, XL:170)
BOTTOM BRACKET	n/a

WHEELS	
RIMS	E-TRA Hookless Tubeless ready Alloy 29 [F] / 27.5 [R] 30mm inner width
HUBS	E-TRA MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 Shimano Micro-Spline Drive Body Pawl Driver (Pawl 36x2 T) Thru-axle [R]
SPOKES	Sapim E-Lite [R] Race [F], e-bike optimized
TIRES	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSORIES	
LIGHTING	Optional:- Giant Recon series e-bike lights available and direct connectable

GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	425	450	475
Seat Tube Angle	77,2° 78,0°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°
Top Tube Length (mm)	577 575	607 605	636 634	665 663
Head Tube Length (mm)	95	100	115	130
Head Tube Angle	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	113,1 108	113,1 108	113,1 108	113,1 108
Wheelbase (mm)	1194 1195	1215 1212	1244 1244	1275 1275
Chain Stay Length (mm)	447 447	447 447	447 447	447 447
Bottom Bracket Drop (mm)	10	10	10	10
Stack (mm)	607 601	611 605	625 619	639 633
Reach (mm)	439 447	457 462	480 487	505 513
Stand Over Height (mm)	726 735	733 742	732 741	741 750
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	50	50
Crank Length (mm)	160	165	165	170
Wheel Size	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

All specifications listed are subject to change without notice.