

TRANCE X ADVANCED E+ ELITE 2

GIANT



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 Magnesium 85Nm, PedalPlus 6-Sensor technology
STEUEREINHEIT	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
AKKU	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Amber Glow/Cordovan
RAHMEN	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
GABEL	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip 3-position Micro Adjust damper, Boost 110x15QR
DÄMPFER	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
KOMponenten	
LENKER	Giant Contact SL 35 Trail, 35x780mm
GRIFFE	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SATTEL	Giant Romero, Neutral
PEDALE	n/a
ANTRIEB	
SCHALTHEBEL	Shimano SLX
UMWERFER	MRP HD2 co-moulded chain guide
SCHALTWERK	Shimano SLX, 12-speed, Shadow+
BREMSEN	Shimano SLX, BR-M7120, 4-piston, hydraulic disc, 203mm [F/R]
BREMSHEBEL	Shimano SLX, I-spec EV
KASSETTE	Shimano, CS-M6100, 10-51T, 12-speed
KETTE	KMC e.12 Turbo, EcoProteq, e-bike optimized
KURBEL	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, S:160, M/L:165, XL:170)
TRETLAGER	n/a

LAUFRÄDER	
FELGEN	E-TRA Hookless Tubeless ready Alloy 29 [F] / 27.5 [R] 30mm inner width
NABE	E-TRA MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 Shimano Micro-Spline Drive Body Pawl Driver (Pawl 36x2 T) Thru-axle [R]
SPEICHEN	Sapim E-Lite [R] Race [F], e-bike optimized
REIFEN	Maxxis Minion DHF 29x2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSORIES	
BELEUCHTUNG	Optional:- Giant Recon series e-bike lights available and direct connectable

GEOMETRIEDATEN

RAHMEN	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Sitzrohrlänge (mm)	400	425	450	475				
Sitzrohrwinkel	77.2°	78.0°	76.0°	76.7°	76.0°	76.7°	76.0°	76.7°
Oberrohrlänge (mm)	577	575	607	605	636	634	665	663
Steuerrohr-Länge (mm)	95	100	115	130				
Steuerrohr-Winkel	65.7°	66.5°	65.8°	66.5°	65.8°	66.5°	65.8°	66.5°
Gabelneigung (mm)	44	44	44	44				
Trail (mm)	113.1	108	113.1	108	113.1	108	113.1	108
Radstand (mm)	1194	1195	1215	1212	1244	1244	1275	1275
Kettenstreben-Länge (mm)	447	447	447	447	447	447	447	447
Tretlager-Höhe (mm)	10	10	10	10				
Stack (mm)	607	601	611	605	625	619	639	633
Reach (mm)	439	447	457	462	480	487	505	513
Überstandshöhe (mm)	726	735	733	742	732	741	741	750
Lenkerbreite (mm)	780	780	780	780				
Vorbaulänge (mm)	40	40	50	50				
Kurbellänge (mm)	160	165	165	170				
Radgrösse	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F				

Spezifikations-, Preis- und Farbänderungen vorbehalten.