

# TRANCE X ADVANCED E+ ELITE 2

**GIANT**

## CARACTÉRISTIQUES TECHNIQUES

TECHNOLOGIE HYBRID	
MOTOR	Giant SyncDrive Pro2 Magnesium 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATTERIE	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRE	
TAILLES	S, M, L, XL
COLORIS	Amber Glow/Cordovan
CADRE	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FOURCHE	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip 3-position Micro Adjust damper, Boost 110x15QR
AMORTISSEUR	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunion mount, custom tuned, recommended sag: 30%
COMPOSANTS	
CINTRE	Giant Contact SL 35 Trail, 35x780mm
POIGNÉES	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCE	Giant Contact SL 35
TIGE DE SELLE	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SELLE	Giant Romero, Neutral
PÉDALES	n/a
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano SLX
DÉRAILLEUR AVANT	MRP HD2 co-moulded chain guide
DÉRAILLEUR ARRIÈRE	Shimano SLX, 12-speed, Shadow+
FREINS	Shimano SLX, BR-M7120, 4-piston, hydraulic disc, 203mm [F/R]
LEVIER DE FREIN	Shimano SLX, I-spec EV
CASSETTE	Shimano, CS-M6100, 10-51T, 12-speed
CHAÎNE	KMC e.12 Turbo, EcoProteq, e-bike optimized
PÉDALIER	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, S:160, M/L:165, XL:170)
PÉDALIER	n/a

ROUES	
JANTES	E-TRA Hookless Tubeless ready Alloy 29 [F] / 27.5 [R] 30mm inner width
MOYEURS	E-TRA MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 Shimano Micro-Spline Drive Body Pawl Driver (Pawl 36x2 T) Thru-axle [R]
RAYONS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSOIRES	
ÉCLAIRAGE	Optional:- Giant Recon series e-bike lights available and direct connectable

## GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	400	425	450	475				
Angle de tube de selle	77,2°   78,0°	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°				
Longueur du tube supérieur (mm)	577   575	607   605	636   634	665   663				
Longueur du tube de direction (mm)	95	100	115	130				
Angle du tube de direction	65,7°   66,5°	65,8°   66,5°	65,8°   66,5°	65,8°   66,5°				
Déport de fourche (mm)	44	44	44	44				
Chasse (mm)	113,1   108	113,1   108	113,1   108	113,1   108				
Empattement (mm)	1194   1195	1215   1212	1244   1244	1275   1275				
Longueur des bases (mm)	447   447	447   447	447   447	447   447				
Hauteur du boîtier de pédalier (mm)	10	10	10	10				
Stack (mm)	607   601	611   605	625   619	639   633				
Reach (mm)	439   447	457   462	480   487	505   513				
Hauteur d'enjambement (mm)	726   735	733   742	732   741	741   750				
Largeur de cintre (mm)	780	780	780	780				
Longueur de potence (mm)	40	40	50	50				
Longueur des manivelles (mm)	160	165	165	170				
Diamètre des roues	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F				

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.