

TRANCE X ADVANCED E+ ELITE 2

GIANT



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Pro2 Mg, 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
PRIKAZ	Giant RideControl GO, frame integrated LED consoleOptional wireless ANT+ display
BATERIJA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
OKVIR	
VELIČINE	S, M, L, XL
BOJE	Sea Sparkle
OKVIR	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
VILICA	Fox 36 Float Performance E-Tuned, 29er, 150mm travel, 44mm offset, Grip Damper, Kabolt-X 110
AMORTIZER	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned
KOMPONENTE	
VOLAN	Giant Contact SL 35 Trail, 35x780mm
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28–30mm (S/M) 142mm Ø29–32mm (L/XL)
LULA VOLANA	Giant Contact SL 35
CIJEV SJEDALA	Tranz-X Rad+ 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SJEDALO	Giant Romero
PEDALE	n/a
POGON	
RUČICE MJENJAČA	Shimano SLX
PREDNJI MJENJAČ	MRP HD2 co-moulded chain guide
STRAŽNJI MJENJAČ	Shimano SLX, 12-speed, Shadow+
KOČNICE	Shimano SLX, BR-M7120, 4-piston, hydraulic disc, 203mm [F/R]
RUČICE KOČNICA	Shimano SLX, I-spec EV
KAZETA	Shimano, CS-M6100, 10-51T, 12-speed
LANAC	KMC e.12 Turbo, EcoProteq, e-bike optimized
POGON	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, S:160, M/L:165, XL:170)
OSOVINA POGONA (BB)	n/a

KOTAČI	
OBRUČI	Giant TRA, Hookless Clincher, 30mm inner width, Hollow Side-Wall Design for improved strength and flat protection
NABE	Giant TRA, E-Drive 260Nm 6-Pawl Driver, 72T engagement, MicroSpline body, 110 x 15 [F], 148 x 12 [R] Thru-axle
ŽBICE	Sapim E-Lite [R] Race [F], e-bike optimized
GUME	Maxxis Minion DHF 29X2.50"" Foldable, TLR, EXO [F] Maxxis Dissector 27.5x2.4"" Foldable, TLR, EXO [R]
DODACI	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
DODACI	
SVJETLA	Optional:- Giant Recon series e-bike lights available and direct connectable

GEOMETRIJA

OKVIR	S	M	L
Dužina cijevi sjedala (mm)	LOW HIGH	LOW HIGH	LOW HIGH
Seat Post Insertion Depth (mm)	220	245	270
Kut cijevi sjedala	77,2° 78,0°	76,0° 76,7°	76,0° 76,7°
Dužina gornje cijevi (mm)	577 575	607 605	636 634
Dužina prednje cijevi (mm)	95	100	115
Kut vilice	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°
Zakrivljenost vilice (offset) (mm)	44	44	44
Staza (mm)	113,1 108	113,1 108	113,1 108
Međuosovinski razmak kotača (mm)	1194 1195	1215 1212	1244 1241
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	447 447	447 447	447 447
Položaj osovine pogona (mm)	10	10	10
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	607 601	611 605	625 619
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	439 447	457 462	480 487
Prekoračna visina (mm)	726 735	733 742	732 741
Širina volana (mm)	780	780	780
Dužina lule volana (mm)	40	40	50
Dužina poluge pedale (mm)	160	165	165
Veličina kotača	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]

Sve navedene specifikacije podložne su promjeni bez prethodne najave.