



SPECS

| HYBRID CYCLING TECHNOLOGY         |                                                                                                                                                            |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MOTOR                             | Giant SyncDrive Pro2 Mg, 85Nm, PedalPlus 6-Sensor technology                                                                                               |
| SENSOR                            | Giant RideControl Ergo3, grip integrated remote                                                                                                            |
| DISPLAY                           | Giant RideControl GO, frame integrated LED consoleOptional wireless ANT+ display                                                                           |
| BATTERY                           | Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible |
| CADRU                             |                                                                                                                                                            |
| MARIMI                            | S, M, L, XL                                                                                                                                                |
| CULORI                            | Sea Sparkle                                                                                                                                                |
| CADRU                             | Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system                      |
| FURCA                             | Fox 36 Float Performance E-Tuned, 29er, 150mm travel, 44mm offset, Grip Damper, Kabolt-X 110                                                               |
| SOC                               | Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned                                                             |
| COMPONENTE                        |                                                                                                                                                            |
| GHIDON                            | Giant Contact SL 35 Trail, 35x780mm                                                                                                                        |
| GRIPS                             | Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)                                                                             |
| PIPA                              | Giant Contact SL 35                                                                                                                                        |
| TIJA SA                           | Tranz-X Rad+ 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)                                                                     |
| SA                                | Giant Romero                                                                                                                                               |
| PEDALE                            | n/a                                                                                                                                                        |
| SISTEMUL DE SCHIMBARE A VITEZELOR |                                                                                                                                                            |
| MANETE SCHIMBATOR                 | Shimano SLX                                                                                                                                                |
| SCHIMBATOR FATA                   | MRP HD2 co-moulded chain guide                                                                                                                             |
| SCHIMBATOR SPATE                  | Shimano SLX, 12-speed, Shadow+                                                                                                                             |
| FRANE                             | Shimano SLX, BR-M7120, 4-piston, hydraulic disc, 203mm [F/R]                                                                                               |
| MANETE FRANA                      | Shimano SLX, I-spec EV                                                                                                                                     |
| PINIOANE                          | Shimano, CS-M6100, 10-51T, 12-speed                                                                                                                        |
| LANT                              | KMC e.12 Turbo, EcoProteq, e-bike optimized                                                                                                                |
| ANGRENAJ                          | Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, S:160, M/L:165, XL:170)                                                      |
| BOTTOM BRACKET                    | n/a                                                                                                                                                        |

| ROTI        |                                                                                                                   |
|-------------|-------------------------------------------------------------------------------------------------------------------|
| JANTE       | Giant TRA, Hookless Clincher, 30mm inner width, Hollow Side-Wall Design for improved strength and flat protection |
| BUTUCI      | Giant TRA, E-Drive 260Nm 6-Pawl Driver, 72T engagement, MicroSpline body, 110 x 15 [F], 148 x 12 [R] Thru-axle    |
| SPITE       | Sapim E-Lite [R] Race [F], e-bike optimized                                                                       |
| ANVELOPE    | Maxxis Minion DHF 29X2.50"" Foldable, TLR, EXO [F] Maxxis Dissector 27.5x2.4"" Foldable, TLR, EXO [R]             |
| EXTRAS      | Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied                                            |
| ACCESSORIES |                                                                                                                   |
| LIGHTING    | Optional:- Giant Recon series e-bike lights available and direct connectable                                      |

GEOMETRIE

| CADRU                          | S                 | M                 | L                 | XL                |
|--------------------------------|-------------------|-------------------|-------------------|-------------------|
|                                | LOW   HIGH        | LOW   HIGH        | LOW   HIGH        | LOW   HIGH        |
| Seat Tube Length (mm)          | 400               | 425               | 450               | 475               |
| Seat Post Insertion Depth (mm) | 220               | 245               | 270               | 295               |
| Seat Tube Angle                | 77,2°   78,0°     | 76,0°   76,7°     | 76,0°   76,7°     | 76,0°   76,7°     |
| Top Tube Length (mm)           | 577   575         | 607   605         | 636   634         | 665   663         |
| Head Tube Length (mm)          | 95                | 100               | 115               | 130               |
| Head Tube Angle                | 65,7°   66,5°     | 65,8°   66,5°     | 65,8°   66,5°     | 65,8°   66,5°     |
| Fork Rake (mm)                 | 44                | 44                | 44                | 44                |
| Trail (mm)                     | 113,1   108       | 113,1   108       | 113,1   108       | 113,1   108       |
| Wheelbase (mm)                 | 1194   1195       | 1215   1212       | 1244   1244       | 1275   1275       |
| Chain Stay Length (mm)         | 447   447         | 447   447         | 447   447         | 447   447         |
| Bottom Bracket Drop (mm)       | 10                | 10                | 10                | 10                |
| Stack (mm)                     | 607   601         | 611   605         | 625   619         | 639   633         |
| Reach (mm)                     | 439   447         | 457   462         | 480   487         | 505   513         |
| Stand Over Height (mm)         | 726   735         | 733   742         | 732   741         | 741   750         |
| Handlebar Width (mm)           | 780               | 780               | 780               | 780               |
| Stem Length (mm)               | 40                | 40                | 50                | 50                |
| Crank Length (mm)              | 160               | 165               | 165               | 170               |
| Wheel Size                     | 29" [F] 27.5" [R] | 29" [F] 27.5" [R] | 29" [F] 27.5" [R] | 29" [F] 27.5" [R] |

Toate specificatiile enumerate se pot schimba fara notificare prealabila.