



CARACTÉRISTIQUES TECHNIQUES

TECHNOLOGIE HYBRIDE	
MOTEUR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
CONTRÔLE	Giant RideControl Ergo3, grip integrated remote
ÉCRAN	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATTERIE	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGEUR	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRE	
TAILLES	S, M, L, XL
COULEURS	Messier/Panther
CADRE	Advanced-grade composite frame, AluXX SL-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FOURCHE	Marzocchi Bomber Z2 E-Tuned, 29er, 150mm travel, 44mm offset, RAIL damper Sweep-Adj, Kabolt 110
AMORTISSEUR (SHOCK)	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPOSANTES	
GUIDON	Giant Contact SL 35 Trail, 35x780mm
POIGNÉES	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCE	Giant Contact SL 35
TIGE DE SELLE	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SELLE	Giant Romero, Neutral
PÉDALES	n/a
TRANSMISSION (DRIVETRAIN)	
LEVIER DE VITESSE	Shimano Deore
DÉRAILLEUR AVANT	MRP HD2 co-moulded chain guide
DÉRAILLEUR ARRIÈRE	Shimano Deore 12-speed, Shadow+
FREINS	Shimano BR-MT420, 4-piston, hydraulic disc, 203mm [F/R]
LEVIER DE FREIN	Shimano Deore, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CHAÎNE	KMC e.12 Turbo, EcoProteq, e-bike optimized
PÉDALIER	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, S:160, M/L:165, XL:170)
BOÎTIER DE PÉDALIER	n/a

ROUES	
JANTES	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
MOYEUX	Shimano MT410 Boost, Center-Lock, 110x15 [F] 148x12 Shimano Micro-Spline Drive Body Thru-axle [R]
RAYONS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSOIRES	
ÉCLAIRAGE	Optional:- Giant Recon series e-bike lights available and direct connectable

Prix de détail: 7 699,00 \$

GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur du tube de selle (mm)	400		425		450		475	
Angle du tube de selle	77,2°	78,0°	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°
Longueur du tube supérieur (top tube) (mm)	577	575	607	605	636	634	665	663
Longueur du tube de direction (head tube) (mm)	95		100		115		130	
Angle du tube de direction	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°	65,8°	66,5°
Déport (rake) de fourche (mm)	44		44		44		44	
Trail (mm)	113,1	108	113,1	108	113,1	108	113,1	108
Empattement (mm)	1194	1195	1215	1212	1244	1244	1275	1275
Longueur des bases (mm)	447	447	447	447	447	447	447	447
Hauteur du boîtier de pédalier (mm)	10		10		10		10	
Portée Verticale (Stack) (mm)	607	601	611	605	625	619	639	633
Portée Horizontale (Reach) (mm)	439	447	457	462	480	487	505	513
Hauteur du cadre (mm)	726	735	733	742	732	741	741	750
Largeur du Guidon (mm)	780		780		780		780	
Longueur de la Potence (mm)	40		40		50		50	
Longueur des manivelles (mm)	160		165		165		170	
Diamètre des Roues	R27.5" / F		R27.5" / F		R27.5" / F		R27.5" / F	

GIANT Canada se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.