



CARACTÉRISTIQUES TECHNIQUES

TECHNOLOGIE HYBRID	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATTERIE	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRE	
TAILLES	S, M, L, XL
COLORIS	Messier/Panther
CADRE	Advanced-grade composite frame, AluXX SL-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FOURCHE	Marzocchi Bomber Z2 E-Tuned, 29er, 150mm travel, 44mm offset, RAIL damper Sweep-Adj, Kabolt 110
AMORTISSEUR	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPOSANTS	
CINTRE	Giant Contact SL 35 Trail, 35x780mm
POIGNÉES	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCE	Giant Contact SL 35
TIGE DE SELLE	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SELLE	Giant Romero, Neutral
PÉDALES	n/a
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano Deore
DÉRAILLEUR AVANT	MRP HD2 co-moulded chain guide
DÉRAILLEUR ARRIÈRE	Shimano Deore 12-speed, Shadow+
FREINS	Shimano BR-MT420, 4-piston, hydraulic disc,203mm [F/R]
LEVIER DE FREIN	Shimano Deore, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CHAÎNE	KMC e.12 Turbo, EcoProteq, e-bike optimized
PÉDALIER	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, S:160, M/L:165, XL:170)
PÉDALIER	n/a

ROUES	
JANTES	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
MOYEURS	Shimano MT410 Boost, Center-Lock, 110x15 [F] 148x12 Shimano Micro-Spline Drive Body Thru-axle [R]
RAYONS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSOIRES	
ÉCLAIRAGE	Optional:- Giant Recon series e-bike lights available and direct connectable

GÉOMÉTRIE

CADRE	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Longueur de tube de selle (mm)	400	425	450	475
Angle de tube de selle	77,2° 78,0°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°
Longueur du tube supérieur (mm)	577 575	607 605	636 634	665 663
Longueur du tube de direction (mm)	95	100	115	130
Angle du tube de direction	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Déport de fourche (mm)	44	44	44	44
Chasse (mm)	113,1 108	113,1 108	113,1 108	113,1 108
Empattement (mm)	1194 1195	1215 1212	1244 1244	1275 1275
Longueur des bases (mm)	447 447	447 447	447 447	447 447
Hauteur du boîtier de pédalier (mm)	10	10	10	10
Stack (mm)	607 601	611 605	625 619	639 633
Reach (mm)	439 447	457 462	480 487	505 513
Hauteur d'enjambement (mm)	726 735	733 742	732 741	741 750
Largeur de cintre (mm)	780	780	780	780
Longueur de potence (mm)	40	40	50	50
Longueur des manivelles (mm)	160	165	165	170
Diamètre des roues	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.