



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	Giant SyncDrive Pro2 Mg, 85Nm, PedalPlus 6-Sensor technology
COMANDO	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED consoleOptional wireless ANT+ display
BATTERIA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Helios Orange
TELAIO	Advanced-grade composite frame, Aluux SL-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FORCELLA	35 GOLD RL AIR 29" 150 1.125-1.5 265 PM180 15X110 W/O REMOTE (Rockshox)
AMMORTIZZATORE	DELUXE SELECT R AIR 185 52.5 N/A TURNION (Rockshox)
COMPONENTISTICA	
MANUBRIO	Giant Contact SL 35 Trail, 35x780mm
MANOPOLE	Giant Tactal Pro-E, tapered design, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
ATTACCO MANUBRIO	Giant Contact SL 35
REGGISSELLA	Tranz-X Rad+ 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SELLA	Giant Romero
PEDALI	n/a
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Deore
DERAGLIATORE ANTERIORE	MRP HD2 co-moulded chain guide
DERAGLIATORE POSTERIORE	Shimano Deore 12-speed, Shadow+
FRENI	Shimano BR-MT420, 4-piston, hydraulic disc,203mm [F/R]
COMANDI FRENO	Shimano Deore, I-spec EV
PACCO PIGNONI	Shimano CS-M6100-12, 10-51T, 12-speed
CATENA	KMC e.12 Turbo, EcoProteq, e-bike optimized
GUARNITURA	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, S:160, M/L:165, XL:170)
MOVIMENTO CENTRALE	n/a

RUOTE	
CERCHI	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
MOZZI	Shimano MT410 Boost, Center-Lock, 110x15 [F] 148x12 Shimano Micro-Spline Drive Body Thru-axle [R]
RAGGI	Sapim E-Lite [R] Race [F], e-bike optimized
COPERTONI	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRA	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSORI	
ILLUMINAZIONE	Optional:- Giant Recon series e-bike lights available and direct connectable

Prezzo: 5.999,00 €

GEOMETRIA

TELAIO	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Lunghezza Tubo Sella (mm)	400	425	450	475
Profondità inserimento reggisella (mm)	220	245	270	295
Angolo Tubo Sella	77,2° 78,0°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°
Lunghezza Tubo Orizzontale (mm)	577 575	607 605	636 634	665 663
Lunghezza Tubo Sterzo (mm)	95	100	115	130
Angolo Sterzo	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Rake Forcella (mm)	44	44	44	44
Avancorsa (mm)	113,1 108	113,1 108	113,1 108	113,1 108
Interasse (mm)	1194 1195	1215 1212	1244 1244	1275 1275
Lunghezza Carro Posteriore (mm)	447 447	447 447	447 447	447 447
Drop Movimento Centrale (mm)	10	10	10	10
Stack (mm)	607 601	611 605	625 619	639 633
Reach (mm)	439 447	457 462	480 487	505 513
Altezza stand over (mm)	726 735	733 742	732 741	741 750
Larghezza Manubrio c/c (mm)	780	780	780	780
Lunghezza Attacco Manubrio (mm)	40	40	50	50
Lunghezza Pedivella (mm)	160	165	165	170
Dimensione Ruote	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.