

TRANCE X ADVANCED PRO 29 1

GIANT



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Gloss Starry Night / Matte Carbon/Chrome
OKVIR	Advanced-Grade Composite front and rear triangles, 135mm Maestro suspension, flip chip, 12x148mm thru-axle
VILICE	Fox 36 Factory Live Valve, FIT4 damper, 44mm offset, 150mm, 15x110 Kabolt X, custom tuned for Giant
AMORTIZER	Fox Factory Live, 185/55, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact SLR TR35, composite, 780x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
OPORA SEDEŽA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
SEDEŽ	Giant Romero SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM GX Eagle, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM GX Eagle
ZAVORE	SRAM G2 RSC, hydraulic, SRAM CenterLine rotors [F]200mm, [R]180mm
ZAVORNE ROČICE	SRAM G2 RSC
VERIŽNIK	SRAM XG-1275, 10x52
VERIGA	SRAM NX Eagle
GONILKE Z VERIŽNIKI	TruVativ Descendent 6k Eagle, 30t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant TRX 2 Carbon 29 WheelSystem
PESTA	Giant TRX 2 Carbon 29 WheelSystem
NAPERE	Giant TRX 2 Carbon 29 WheelSystem
PLAŠČI	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 TPI, 3C Max Terra, EXO, TR
DODATKI	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	430		430		465		496	
Kot sedežne cevi	77,2° 77,9°		77,2° 77,9°		77,2° 77,9°		77,2° 77,9°	
Top Tube Length (mm)	566 564		597 595		629 627		656 654	
Višina glave okvirja (mm)	95		100		110		120	
Krmilni kot	65,5° 66,2°		65,5° 66,2°		65,5° 66,2°		65,5° 66,2°	
Zamik vpetja osi (mm)	44		44		44		44	
Trail (mm)	125,1 119,5		125,1 119,5		125,1 119,7		125,1 119,5	
Medosna razdalja (mm)	1173		1205		1239		1268	
Dolžina cevi ob verigi (mm)	438		438		438		438	
Bottom Bracket Drop (mm)	40		40		40		40	
Oddaljenost zgornje cevi od gonilne osi (mm)	617		621		631		640	
Doseg (mm)	426		456		486		510	
Višina zgornje cevi (mm)	729		729		752		760	
Širina krmila (mm)	780		780		780		780	
Dolžina opore krmila (mm)	40		40		50		50	
Dolžina gonilke (mm)	165		170		170		170	
Velikost obročnikov	29"		29"		29"		29"	

Vse navedene specifikacije se lahko spremenijo brez obvestila.