

TRANCE X ADVANCED SX

GIANT



SPECIFIKACE

RÁM	
VELIKOSTI	M, L, XL
BARVA	Kelp Forest/Chrome
RÁM	Advanced-Grade Composite front and rear triangles, 145mm Maestro suspension, 12x148mm thru-axle, 27.5-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
VIDLICE	Fox 36 Float Performance Elite, 160mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
TLUMIČ	Fox Float X Performance Elite, two-position LSC adjust, 185/55, custom tuned for Giant
KOMPONENTY	
ŘÍDÍTKA	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GRIPY	Giant Tactal Pro Single Lock-On, 132x35mm
PŘEDSTAVEC	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEDLOVKA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SEDLO	Giant Romero SL
PEDÁLY	-
OSAZENÍ	
ŘAZENÍ	Shimano SLX M-7100, 1x12
PŘESMYKAČ	-
PŘEHAZOVAČKA	Shimano SLX M-7100
BRZDY	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BRZDOVÉ PÁKY	Shimano Deore BL-M6100
KAZETA	Shimano SLX M7100, 10x51
ŘETĚZ	KMC X-12
KLIKY	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
STŘED	Shimano, press fit

KOLA	
RÁFKY	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NÁBOJE	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, MicroSpline driver body
DRÁTY	Sapim, 28, straight pull, DBL Technology
PLÁŠTĚ	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 27.5x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
DOPLŇKY	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Cena: akční cena 113 399 Kč (původně 161 999 Kč)

GEOMETRIE

RÁM	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Délka sedlové trubky (mm)	400			425			450			475		
Max. zasunutí sedlovky (mm)	280			305			330			355		
Úhel sedlové trubky	75,5° 75,9° 76,3°	75,6° 75,9° 76,3°	75,6° 76,0° 76,3°	75,7° 76,0° 76,3°	75,7° 76,0° 76,3°	75,7° 76,0° 76,3°	75,7° 76,0° 76,3°	75,7° 76,0° 76,3°	75,7° 76,0° 76,3°	75,7° 76,0° 76,3°	75,7° 76,0° 76,3°	75,7° 76,0° 76,3°
Délka horní trubky (mm)	574 573 572	605 604 603	627 626 626	660 659 658								
Délka hlavové trubky (mm)	100			105			115			125		
Úhel hlavové trubky	63,1° 63,5° 63,9°	63,2° 63,5° 63,9°	63,2° 63,6° 63,9°	63,3° 63,6° 63,9°	63,3° 63,6° 63,9°	63,3° 63,6° 63,9°	63,3° 63,6° 63,9°	63,3° 63,6° 63,9°	63,3° 63,6° 63,9°	63,3° 63,6° 63,9°	63,3° 63,6° 63,9°	63,3° 63,6° 63,9°
Offset vidlice (mm)	44			44			44			44		
Trail (mm)	143,9 141,1 138,1	143,6 140,8 138	143,3 140,6 137,8	143 140,4 137,8								
Rozvor (mm)	1194 1193 1193	1226 1225 1225	1250 1250 1249	1285 1284 12								
Délka řetězové vzpěry (mm)	440 439 438	440 439 438	440 439 438	440 439 438								
Bottom Bracket Drop (mm)	30 25 21	31 26 21	30 26 21	31 26 21								
Stack (mm)	626 623 621	631 628 625	640 638 635	650 647 644								
Reach (mm)	413 417 421	443 447 451	463 467 471	494 497 501								
Výška rámu od země (mm)	727 731 735	730 734 739	754 751 756	744 749 754								
Délka představce (mm)	40			40			50			50		
Délka klik (mm)	165			170			170			170		
Rozměr kol	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Děláme vše pro to, aby veškeré údaje na tomto webu byly správné a aktuální. Přesto si ale musíme vyhradit právo na případné změny specifikací, barevného provedení a cen, a to bez předchozího upozornění. Děkujeme za pochopení.