

TRANCE X ADVANCED SX

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Kelp Forest/Chrome
FRAME	Advanced-grade composite front and rear triangles, 145mm Maestro suspension, flip chip - Maestro 3, flip chip - headset, 12x148mm thru-axle, integrated downtube storage
FORK	Fox 36 Float Performance Elite, 160mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
SHOCK	Fox Float X Performance Elite, two-position LSC adjust, 185/55, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 20mm rise, alloy, 780x35mm
GRIPS	Giant Tactal Pro single lock-on
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch Adjustable, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L/XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano SLX M-7100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX M-7100
BRAKES	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano Deore BL-M6100
CASSETTE	Shimano SLX M7100, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant TRX WheelSystem, carbon rim, 30mm IW, 40mm OW, 21mm H, Wide Guard technology, [F] 29, [R] 27.5
HUBS	[F] Giant MTB alloy, 6-bolt, sealed [R] Giant MTB alloy, 6 bolt, 72t POE, 6-pawl, sealed
SPOKES	Sapim Laser straight pull, DBL technology
TIRES	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 27.5x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, 3M tailgate protector, integrated down tube storage bag

Suggested Retail Price (CDN): \$6,499.00

FRAME GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	75.5°	75.9°	76.3°	75.6°	75.9°	76.3°	75.6°	76.0°	76.3°	75.7°	76.0°	
Top Tube Length (mm)	574	573	572	605	604	603	627	626	626	660	659	65
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	63.1°	63.5°	63.9°	63.2°	63.5°	63.9°	63.2°	63.6°	63.9°	63.3°	63.6°	
Fork Rake (mm)	44			44			44			44		
Trail (mm)	143.9	141.1	138.1	143.6	140.8	138	143.3	140.6	137.8	143	140.4	1
Wheelbase (mm)	1194	1193	1193	1226	1225	1225	1250	1250	1249	1285	1284	
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	43
Bottom Bracket Drop (mm)	30	25	21	31	26	21	30	26	21	31	26	21
Stack (mm)	626	623	621	631	628	625	640	638	635	650	647	64
Reach (mm)	413	417	421	443	447	451	463	467	471	494	497	50
Stand Over Height (mm)	727	731	735	730	734	739	754	751	756	744	749	75
Stem Length (mm)	40			40			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

All prices and specifications are subject to change without notice.