

TRANCE X ADVANCED SX

GIANT



SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Kelp Forest/Chrome
TELAIO	Advanced-Grade Composite front and rear triangles, 145mm Maestro suspension, 12x148mm thru-axle, 27.5-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FORCELLA	Fox 36 Float Performance Elite, 160mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
AMMORTIZZATORE	Fox Float X Performance Elite, two-position LSC adjust, 185/55, custom tuned for Giant
COMPONENTISTICA	
MANUBRIO	Giant Contact TR35, alloy, 780x35mm, 20mm rise
MANOPOLE	Giant Tactal Pro Single Lock-On, 132x35mm
ATTACCO MANUBRIO	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
REGGISELLA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLA	Giant Romero SL
PEDALI	N/A
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano SLX M-7100, 1x12
DERAGLIATORE ANTERIORE	N/A
DERAGLIATORE POSTERIORE	Shimano SLX M-7100
FRENI	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
COMANDI FRENO	Shimano Deore BL-M6100
PACCO PIGNONI	Shimano SLX M7100, 10x51
CATENA	KMC X-12
GUARNITURA	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
MOVIMENTO CENTRALE	Shimano, press fit

RUOTE	
CERCHI	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
MOZZI	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, MicroSpline driver body
RAGGI	Sapim, 28, straight pull, DBL Technology
COPERTONI	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 27.5x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRA	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Prezzo: 6.499,00 €

GEOMETRIA

TELAIO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Lunghezza Tubo Sella (mm)	400			425			450			475
Profondità inserimento reggisella (mm)	280			305			330			355
Angolo Tubo Sella	75,5°	75,9°	76,3°	75,6°	75,9°	76,3°	75,6°	76,0°	76,3°	75,7°
Lunghezza Tubo Orizzontale (mm)	574	573	572	605	604	603	627	626	626	660
Lunghezza Tubo Sterzo (mm)	100			105			115			125
Angolo Sterzo	63,1°	63,5°	63,9°	63,2°	63,5°	63,9°	63,2°	63,6°	63,9°	63,3°
Rake Forcella (mm)	44			44			44			44
Avancorsa (mm)	143,9	141,1	138,1	143,6	140,8	138	143,3	140,6	137,8	143
Interasse (mm)	1194	1193	1193	1226	1225	1225	1250	1250	1249	1285
Lunghezza Carro Posteriore (mm)	440	439	438	440	439	438	440	439	438	440
Drop Movimento Centrale (mm)	30	25	21	31	26	21	30	26	21	31
Stack (mm)	626	623	621	631	628	625	640	638	635	650
Reach (mm)	413	417	421	443	447	451	463	467	471	494
Altezza stand over (mm)	727	731	735	730	734	739	754	751	756	744
Lunghezza Attacco Manubrio (mm)	40			40			50			50
Lunghezza Pedivella (mm)	165			170			170			170
Dimensione Ruote	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.