

TRANCE X E+ 1 2023

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
COMANDO	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATTERIA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CARICATORE	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNETTIVITÀ	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Cold Night / Cobalt
TELAIO	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
FORCELLA	Fox 36 Float Performance E-Tuned, 29er, 150mm travel, 44mm offset, Grip 3-position Micro Adjust damper, Kabolt-X 110
AMMORTIZZATORE	FOX FLOAT X PERFORMANCE AIR 185/52.5 BLK 2POS TRUNNION
COMPONENTISTICA	
MANUBRIO	Giant Contact 35 Trail, 35x780mm
MANOPOLE	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
ATTACCO MANUBRIO	Giant Contact SL 35
REGGISELLA	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SELLA	Giant Romero E
PEDALI	Flat pedal
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Deore XT
DERAGLIATORE ANTERIORE	MRP HD2 co-moulded chain guide
DERAGLIATORE POSTERIORE	Shimano Deore XT, 12-speed, Shadow+
FRENI	Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 220mm [F], 203mm [R]
COMANDI FRENO	Shimano Deore XT, I-spec EV
PACCO PIGNONI	Shimano CS-M7100-12, 10-51T, 12-speed
CATENA	KMC e.12 Turbo, EcoProteq, e-bike optimized
GUARNITURA	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
MOVIMENTO CENTRALE	n/a

RUOTE	
CERCHI	Giant AM30, Tubeless ready, 30mm inner width, 29"
MOZZI	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAGGI	Sapim E-Lite [R] Race [F], e-bike optimized
COPERTONI	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRA	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORI	
LUCCHETTO	Torx 25 Battery Lock with built-in Torque limiter

Prezzo: € 6.299

GEOMETRIA

TELAIO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Lunghezza Tubo Sella (mm)	400		425		450		475	
Angolo Tubo Sella	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°
Lunghezza Tubo Orizzontale (mm)	577	575	610	605	637	635	667	665
Lunghezza Tubo Sterzo (mm)	95		100		110		120	
Angolo Sterzo	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°	65,8°	66,5°
Rake Forcella (mm)	44		44		44		44	
Avancorsa (mm)	117	122,4	117	122,4	117	122,4	117	122,4
Interasse (mm)	1205	1206	1239	1237	1268	1269	1300	1301
Lunghezza Carro Posteriore (mm)	473	473	473	473	473	473	473	473
Drop Movimento Centrale (mm)	30	20	30	20	30	20	30	20
Stack (mm)	606	601	611	605	621	614	630	624
Reach (mm)	439	447	457	462	482	489	510	517
Altezza stand over (mm)	783	789	775	784	763	770	775	782
Larghezza Manubrio c/c (mm)	780		780		780		780	
Lunghezza Attacco Manubrio (mm)	40		50		50		60	
Lunghezza Pedivella (mm)	160		165		165		170	
Dimensione Ruote	29"		29"		29"		29"	

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.