TRANCE X E+ 1



SPECS

HYBRID CYCLING TECHNOLOGY (PEDAL ASSIST)	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
CONTROLLER	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED displayANT+ Wireless display compatible
BATTERY	EnergyPak Smart 750Wh, EnergyPak Plus range extender compatible
CHARGER	EnergyPak 6A smart charger
FRAME	
SIZES	S, M, L, XL
COLOURS	Gloss Amber Glow
FRAME	ALUXX SL-Grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH derrailleur hanger, Giant EnergyPak Plus Range Extender Compatible
FORK	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip Damper, Boost 110x15QR, e-optimised
SHOCK	Fox Float X Performance, EVOL Large Volume sleeve, 3-Pos Lever, 185x52.5mm Trunnion mount
COMPONENTS	
HANDLEBAR	Giant Contact 35 Trail, 35x780mm
GRIPS	Giant Tactal Pro-E, single lock-on
STEM	Giant Contact SL 35
SEATPOST	Giant Contact Switch, dropper, 30,9mm (S:125, M: 150, L/XL:170)
SADDLE	Giant Romero Trail
PEDALS	Flat pedal
DRIVETRAIN	
SHIFTERS	Shimano Deore XT
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano Deore XT, 12-speed, Shadow+
BRAKES	Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 220mm
BRAKE LEVERS	Shimano Deore XT BL-M8100, I-spec EV
CASSETTE	Shimano CS-M7100-12, 10-51T, 12-speed
CHAIN	KMC e.12 Turbo, EcoProteq, e-bike optimised
CRANKSET	Praxis WaveTM 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
BOTTOM BRACKET	-

WHEELS	
RIMS	Giant AM 29", Tubeless ready, 30mm inner width
HUBS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPOKES	Sapim E-Lite [R] Race [F]
TYRES	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO, 3c MaxxTerra[F] Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 120tpi 3C [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LOCK	Torx 25 Battery Lock with built-in Torque limiter

Price: £6,299.00

GEOMETRY

FRAME	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	400	425	450	475
Seat Tube Angle	76.0° | 76.7°	76.0° | 76.7°	76.0° | 76.7°	76.0° | 76.7°
Top Tube Length (mm)	577 | 575	610 | 605	637 | 635	667 | 665
Head Tube Length (mm)	95	100	110	120
Head Tube Angle	65.7° | 66.5°	65.8° | 66.5°	65.8° | 66.5°	65.8° | 66.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	117 | 122.4	117 | 122.4	117 | 122.4	117 | 122.4
Wheelbase (mm)	1205 | 1206	1239 | 1237	1268 | 1269	1300 | 1301
Chain Stay Length (mm)	473 | 473	473 | 473	473 | 473	473 | 473
Bottom Bracket Drop (mm)	30 | 20	30 | 20	30 | 20	30 | 20
Stack (mm)	606 | 601	611 | 605	621 | 614	630 | 624
Reach (mm)	439 | 447	457 | 462	482 | 489	510 | 517
Stand Over Height (mm)	783 | 789	775 | 784	763 | 770	775 | 782
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	50	50
Crank Length (mm)	160	165	165	170
Wheel Size	29"	29"	29"	29"

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.